

Index *(bold italics for definitions) should/can be changed, not documented changes $b \leftrightarrow n$ & $b \rightarrow$ italics*

- A** priori / a posteriori probability **438, 549**
Absolute probability \rightarrow State probability
Absolutely continuous **440, 451**
Absorbing state **197, 198, 509-10**
AC parameters 88-90
Accelerated test 35, 81, 86, **98-99**, 101, **341-46**, 347-48, **376**, 386, 464, 574 (see also **Burn-in**)
Acceleration factor **36-37**, 99, 103, **341-46**, 373, **376**
• at assembly level **376**
Acceptable Quality Level (AQL) **86, 318-20, 568**
Acceptable risk/safety level **10-11, 310**
Acceptance line **317, 334-36, 566-67**
Acceptance probability curve **565-66**
 \rightarrow Operating characteristic curve
Acceptance test 18, 255, **314, 332, 325, 408-09**, 412 (see also **Demonstration**)
Accessibility 8, **116, 157**
Accident/disaster **299, 300, 301-09** (see also External event, Harm, *MTTA*, Safety function)
Accident prevention **9, 399**
Accumulated operating time \rightarrow Cumulative op. time
Accumulated reward **271, 279, 517**
Achieved reliability/maintainability **8, 115, 321**
Acquisition cost 11, **13, 14, 391**, 408
Activation energy 37, 86, 97, 99, 103, **109, 341-43**, 373
Active redundancy 31, **43**, 43-61, **62**, 64, 68, 76, 196, **201**, 213, 217, 232, **233, 397**, 504, **508-10**
• with common cause failures **271-74**
Addition theorem **435-36, 437-38**, 466
Additional / supplementary states **193-95, 531**
Adjustment **116, 120, 158**
Administrative delay **8, 113, 387, 394**
Advantage of
• fail-safe procedure **66, 72, 79, 120, 158, 160, 164, 303, 305, 306, 308, 309**
• in-circuit test **374**
• only one repair crew **121, 171, 200, 204, 207, 217, 218, 240, 386** (see also Only one repair crew)
• redundancy (nonrepairable) **44**
• repair priority **222 (220 for possible problems)**
• repairable redundancy **202**
• 100% incoming inspection **370-71**
(see also Realize an advantage)
Aerospace 403, 404
Aftereffect \rightarrow Without aftereffect
After-sale 8, **13, 115, 413**
Age replacement **134, 135-40**
Aging **6, 442-43** (see also Wear-out, As-bad-as-old)
Alarm / alarm circuitry **49, 158, 249, 255, 298**, 310
Alarm defection **255**
Alignment \rightarrow Adjustment
Allocation (reliability) **67, 408, 410, 421**
All-terminal **275-76**
Alternating renewal process (**ARP**) **171, 176, 490-93**, 494, 521, **523, 525**
Alternative hypothesis (H_1) 314, 325, 332, 339, 346, **563-64**
Alternative investigation methods **280-94**
AMSAA model **364**
Analog \rightarrow Linear
Anderson - Darling statistic **573**
Antistatic **94, 153** (see also Electrostatic discharge)
AOQ/AOQL 315-16
Aperture in shielded enclosure **149**
Approximate expressions 124, **174**, 186-87, **198-99, 201-02, 206-07**, 213, **215, 217, 226, 230, 232, 233, 237, 243, 245, 247, 251, 279, 293-94, 296-309, 460, 468, 520, 529, 532**
Approximation for
• distribution function **7, 193, 444, 463, 468, 472-75**, 485-87, **531**, 546-47
• interval reliability **172, 183, 200, 217, 278, 524**
• Laplace transform 186, **206, 528**
• $MTTF_S$, MUT_S , MDT_S **121-24, 199, 200, 201, 206, 217, 232, 233, 237, 269, 270, 279, 293, 294, 516**
• point availability **61, 183, 186-87, 195, 198, 201, 206, 215, 217, 232, 233, 293-94, 297, 528, 529**
• reliability function **199, 201, 278, 294**
• repair function **114-15, 186, 206-07, 528**
• series-parallel structures **232, 233**
• spare parts **126-30**
AQL \rightarrow Acceptable Quality Level
Arbitrary failure and repair rates **171, 176-82, 188, 193-95, 207-13, 531**
Arbitrary initial conditions (one item) **184-87**
Arbitrary repair rate **171, 183, 188, 192-95, 204-13, 218-19, 220, 222-25, 249-50, 526-30**
Arithmetic random variable **440, 443, 454, 466-70**
ARP \rightarrow Alternating renewal process
Arrhenius model **36-37, 97, 102, 341-44, 373**
Arrival rate 532, 540 (see also Intensity)
Arrival/occurrence time 355, **365, 480, 533, 534**
As-bad-as-old 134, **138-39, 365, 387, 443, 535, 565**
As-good-as-new 2, **3, 5** 6, 8, 41, **61, 122, 123, 134, 171, 173, 175, 178, 238-40, 241, 250, 265, 328, 353, 386, 387, 390-93, 442, 443, 479, 536**
Aspect oriented programming 164
Assessed reliability **3** (see also **Demonstration, Estimation**)
Assumptions **26, 31, 39, 41, 43, 52, 170-71, 229, 238-40, 260, 323, 328, 330, 356, 429, 442, 449**
Assurance program / tasks \rightarrow RAMS assurance progr.

- Asymptotic behavior
 - alternating renewal processes (ARP) 493
 - Markov processes (MP) 512-14, 526
 - one-item structure 185-87
 - regenerative processes (RGP) 495, 530
 - renewal processes (RP) 485-87
 - semi-Markov processes (SMP) 524-26
 - versus stationary/steady-state 187, 488, 493, 495, 513, 514, 524, 525, 530
(see also Stationary/steady-state)
- Asynchronous logic 155
- Attainable intensity 366
- Attributes (software), 160, 161, 162, 164
- Attributes (test by) 311
- Audits 21, 107, 160, 370, 387, 402, 412, 413, 417
- Availability 9, 16, 386 → Point availability (PA(*t*))
(see also Average, Intrinsic, Joint, Mission, Operational, Overall, Technical, Work-mission av.)
 - approximate expressions 178, 183, 187, 198, 217, 232, 233, 248, 256, 274, 529, 532
- Availability estimation and demonstration 323-27, 561-62, 569-71
- Average availability 9, 178-79, 183, 184, 188, 514, 525
- Average Outgoing Quality (AOQ) 315-16
- Avoid
 - common cause failures 274
 - external events → Barrier, Risk avoidance/mitig.
 - human errors 158-59, 294-310
 - secondary failures → Secondary failures
(see also Negligible)
- Axioms of probability theory 432
- Backdriving 374**
- Backward equation → Kolmogorov equation
- Backward recurrence time 485, 486
(see also Forward)
- Bad-as-old (BAO) → As-bad-as-old
- Bamboo structure 97
- Barriers 76, 286, 299-300, 302-09, 310
- Baseline → Reference documentation
- Basic rules → Rules for
- Bathtub curve 6-7, 460
- Bayes theorem 438, 452, 549
- Bayesian estimate/statistics 452, 549
- BDD → Binary decision diagram
- Becomes negligible → Negligible
- Bernoulli distribution → Binomial distribution
- Bernoulli trials/model 315, 465, 469, 471, 551, 554
- Bernoulli variable 465, 469
- Beta distribution/function 467, 556, 580, 582
- Biased 323, 329, 330, 545, 551, 553, 571
(see also Unbiased)
- Bi-directional connection 31, 53, 275, 276
- Bienaymé → Chebyshev
- Binary decision diagram (BDD) 53, 58, 76, 283-85
- Binary process 56, 58, 61, 179, 327, 531 (see also Indicator)
- Binomial distribution 44, 312-16, 322, 353, 446-47, 465-67, 543, 551, 554-57, 565
- Binomial expansion 329
- Birth and death process 131, 197, 214-17, 517-21
- Birth processes → Birth and death process
- BIST → Built-in self-test
- BIT → Built-in test
- BITE → Built-in test equipment
- Bivariate distribution 452
- Black model 97, 345
- Blackwell theorem 486
- Block replacement 134, 135, 136-40
- Bonding 93, 95, 100, 103, 104
- Boolean function method 57-61, 275, 280, 281, 283
- Boolean variable 58, 327 (see also Indicator)
- Bottom-up 72, 78, 163, 164, 166, 286, 390
(see also Top-down)
- Boundary-scan 155
- Boundary sliding → Grain boundary sliding
- Bounds 59, 61, 187, 215, 229, 240, 260, 264, 265, 280, 293-94 (see also Interval estimation)
- Branching processes 538
- Breakdown 96-97, 102, 106, 145, 149, 150
- Bridge structure 31, 53-54
- Bridging 90
- Built in/into 1, 2, 8, 16, 115, 144, 154, 259
- Built-in self-test (BIST) 156
- Built-in test/test equipment (BIT/BITE) 66, 116-18, 156, 249, 252, 255, 256
- Burn-in 6-7, 89, 101, 111, 371, 372, 373, 376, 386
(see also Dynamic burn-in, Static burn-in)
- Bypass 158, 294, 295, 310 (see also Incomplete human performance, Risk management)
- Calibration 370**
- Capability (performance) 13, 33, 387, 388, 400
- Capacitors
 - use & limits 100, 145, 146, 148, 151, 589
 - test/screening 372
- Captured 188
- Care (pay attention) 29, 38, 42, 66, 111, 174, 220, 249, 280, 295, 353-54, 357, 362, 363, 365, 368, 375, 540 (see also Design guidelines, Mandatory, Rules, Model validity)
- CASE 164
- Case-by-case 35, 81, 138, 139, 174, 220, 238, 240, 249, 259, 266, 274, 277, 289, 346, 375, 524, 526
- Cauchy distribution 579

- Cause-to-effects-analysis / chart 10, 15, 22, 23, 66, 72-80, 160, 165, 363, 389-91
- Causes for
- common cause failures 271
 - damage 74-75, 85, 94, 151, 152, 363, 371, 374
 - hardware defects/failures 3-4, 95, 103, 106-07, 109-11, 271, 363, 374-75, 388, 389, 399, 427
 - software defects 162-65
 - weaknesses 162-65, 363
- CCF → Common cause failure
- CDM → Charged device model
- Censoring (time (type I), failure (type II))
- data analysis 329, 330, 331, 332, 356-61, 365, 366, 534, 542, 553, 558, 559
 - reconfigurable systems 38, 259-71 (see also Phased)
- Central limit theorems 126, 472-75, 487, 544
- Central moments 449
- Centralized logistic support 125-29, 130
- Ceramic capacitor 145, 148, 151, 153, 589
- Cerdip 85, 147
- Certification 402
- Change 7, 21, 87, 115, 119, 165, 166, 363, 369, 387, 412, 413, 418, 425, 427 (see also Modification)
- Chapman-Kolmogorov equations 498
- Characteristic function 577, 583
- Characterization (electrical) 89, 90, 91-93, 108
- Charge spreading 103
- Charged device model (CDM) 94
- Chebyshev inequality 327, 449, 471, 472, 550
- Check list 77, 79, 120, 409, 410-13, 414-20, 421-25
- Check strategy 21, 249, 250, 254, 255, 256, 257-58
- Chi-square (χ^2) distribution 350-52, 359-61, 446-47, 461, 573-76, 578
- relation to exponential, normal, Poisson distributions 461, 468, 578
- Chi-square (χ^2) test 350-52, 356, 573-76
- Claim 10, 15, 395 (see also Product liability)
- Classical probability 433
- Cleaning 152, 153, 157, 589
- Clock 149, 151, 155, 156
- Close cooperation → Cooperation
- Clustering of states 229, 293
- CMOS terminals/technology 148, 150, 591
- Coating 93, 147
- Coefficient of variation 128, 449, 457-69
- Coffin-Manson 111, 345 (see also Paris law)
- Cognitive 294, 295
- Coherent system 57, 58, 59, 61, 293, 531-32
- Cold redundancy → Standby redundancy
- Combination of
- methods / tools / models 38, 76-78, 161, 220, 282, 286, 295, 310, 391
 - stresses 69-72, 82, 111, 345-46
- Commercial computation programs 35, 281, 290
- Common cause
- events 286
 - failures 42, 45, 66, 72, 79, 255, 271-74, 277, 286, 397, 422 (see also Single-point failures)
- Common ground point 148
- Common mode currents 149
- Common mode failures 66, 72, 271, 277
- Communication 11, 299, 310, 398
- Comparative studies / comparisons 14-15, 26, 31, 38, 44, 47-48, 78, 117, 130, 202, 206, 207, 217-18, 227, 232-33, 237, 272-73, 378, 408, 415, 484, 588-91
- Compatibility 144, 148, 151, 154, 162, 418, 424, 428
- Complementary event 430
- Complete Gamma function 459, 460, 582
- Completeness (software) 162
- Complex structure/system 31, 52, 53-61, 64-66, 68-69, 238-40, 243-79, 280-92, 293-94, 294-310
- Complexity factor 67
- Components & materials 81-86, 150-53, 423, 588-91 (see also Compatibility, Design guidelines, Technological properties/limits)
- Composite hypotheses 563
- Composite shmoo-plot 91
- Compound failure rate (λ_{Co}) 65, 343-44
- Compound processes → Cumulative processes
- Compression → Time compression
- Compromises / controversial 10, 221, 310 (see also Cooperation)
- Computer-aided reliability prediction 35, 282, 289-92
- Concept of probability 431-34
- Conclusions (for repairable systems) 174
- Concurrent engineering 11, 16, 19, 387, 391, 396, 414
- Conditional
- density/distrib. function 452, 523, 533, 549
 - failure rate 40, 390, 442
 - mean / expected value 442, 453
 - probability 7, 44, 390, 434-35, 441, 442, 482
 - reliability function 40, 397, 442
 - state probability 498
- Conditions for (see also Model validity)
- Markov processes 170, 171, 277, 386, 478, 496, 498, 503, 522, 526
 - memoryless property 40, 390, 442-43, 458, 498
 - Poisson processes (HPP & NHPP) 488, 532
 - regeneration point / state 386, 494
 - regenerative processes 494
 - renewal processes 479-80
 - semi-Markov processes 171, 386, 478, 521, 522
 - semi-regenerative processes 171, 386, 494, 530
- Conductive-filament 345
- Confidence ellipse 312-13, 556-57
- Confidence interval 312-13, 324, 330-31, 554, 555-57

- Confidence level 86, 312, 330, 554, 562
- Confidence limits 554
- availability $PA=AA$ 323, 324, 561-62
 - failure rate λ 330-32, 558-61
 - failure rate at system level λ_S 332
 - one sided 314, 324, 331, 554, 562
 - parameters of a lognormal distribution 339
 - unknown probability p 312-14, 554-58
(in particular 313, 324, 331, 554)
- Configuration 387, 417, 424 (see also Documentation)
- Configuration accounting 21, 412, 418
- Configuration auditing 21, 412, 417-18 (see also Design reviews)
- Configuration control 21, 165, 412, 418
- Configuration identification 21, 412, 417
- Configuration management 13, 15, 16, 17, 18, 21, 159, 160, 164, 165, 370, 387, 417-19, 424
- Conformal coating \rightarrow Coating
- Congruential relation 291
- Conjunctive normal form 59
- Connections 157
- Connector 145, 150, 151, 153, 156, 157
- Consecutive k -out-of- n systems 45
- Consequence \rightarrow Fault effect
- Consistency (software) 162
- Consistency checks 76
- Consistency condition 477
- Consistent estimates 472, 549, 550
- Constant acceleration test 373
- Constant failure rate λ
- as necessary condition 6, 40, 171, 179, 226-310, 328-37, 393, 408, 442-43, 458, 503-06, 498-521
 - at system level λ_{S0} 177, 232, 233, 323, 390, 458
 - concept 6, 328, 443, 457-58, 488-89, 498-521
 - estimation 329, 330-32, 551, 553, 558-60
 - demonstration 332-37
 - investigations/results 6, 35, 40, 61-64, 183, 187, 188, 189-93, 196-207, 214-37, 245-74, 277-79, 293-310, 328-37, 442-43, 457-58, 488, 498-521, 526-30, 551, 558-60
(in particular 179, 183, 186-87, 188, 195, 201, 213, 217, 232, 233, 235, 267, 331, 335, 442-43)
- Constant repair rate μ 183, 188, 189-91, 196-204, 214-18, 220-22, 225-37, 245-48, 251-74, 277-79, 293-310, 498-521
(in particular 183, 186-87, 188, 195, 201, 217, 232, 233, 235, 267)
- Constant versus random variable 440
- Consumer risk β 315, 318, 325, 326, 333, 335, 564, 567, 570 (see also Type I/II error)
- Contamination 85, 93, 98, 103, 152, 153, 371
- Continuity test 88
- Continuous from the right 5, 439, 480, 481, 543
- Continuous parameter MC 498 \rightarrow Markov process
- Continuous random variable 440, 446, 451, 457-64
- Contract 18, 401, 410 (see also System specs.)
- Controllability 155
- Convergence almost sure \rightarrow Conv. with probability 1
- Convergence in probability 471, 472, 549
- Convergence quickness 127, 183, 186-87, 198, 199, 313, 324, 331, 432, 544, 545-46, 557, 560
- $\hat{F}(t) \rightarrow F(t)$ 545-46
 - $\hat{p}=k/n \rightarrow p$ 313, $PA \rightarrow PA$ 324, $\hat{\lambda}=k/T \rightarrow \lambda$ 331
 - $PA_{S0}(t) \rightarrow PA_S$ 183, 186-87, 198
 - $R_{S0}(t) \rightarrow e^{-\lambda_{S0}t}$ 199
- Convergence with probability one 471, 472, 543, 549
- Convolution 454-56, 481, 491, 583
- Cooling 82, 84, 145-47, 150, 262, 274, 275, 363, 373
- Cooperation 10, 16, 19, 20, 21, 92, 238, 280, 300, 404, 406, 410-13 (see also Compromise, Teamwork)
- Corrective actions 16, 22, 72, 73, 77, 80, 104-05, 160, 370, 396, 398, 420, 425, 428
(see also Quality data reporting system)
- Corrective maintenance 8, 112-13, 118, 120, 387
(see also Repair)
- Correlation coefficient 453, 463, 479
- Correlation diagram 78
- Correspondence \rightarrow Equivalence
- Corrosion 6, 64, 83, 85, 98-100, 103, 104, 147, 345
- Cost / cost equations 12, 14, 67, 135-40, 142-43, 378, 379-83, 466, 514
- Cost effectiveness 11, 13, 16, 321, 363, 378, 379-83, 388, 391, 400, 402
- Cost optimization 11-15, 16, 67, 120, 134-40, 142-43, 242, 376-83, 388, 391, 400, 408, 413, 414, 418, 420, 466, 514, 539
- Cost rate / cost per unit time 12-14, 135-40
- Count function/process 5, 355, 480, 488, 532, 538
- Coupler 266 (see also Switching)
- Coupling 91, 97, 148, 151, 589
- Covariance matrix 453
- Coverage 90, 91, 95, 117, 249, 252 (see also Incomplete coverage, Test coverage)
- Cracks 85, 93, 103, 104, 107, 108-11, 152, 153, 345
- Cramér - von Mises test 356, 572
- Creep 3, 101, 69, 109
- Crimping 157
- Critical
- application/decision/parts 1, 4, 26, 66, 72, 84, 87, 101, 109, 144-68, 249, 254, 294, 295, 310, 370
 - design review (CDR) 108, 419, 425
 - failure 1, 4, 9, 69, 72, 73, 76, 78, 120, 158, 168, 300, 301, 303-09, 310, 390, 411
 - operating states 277
 - remark/discussion 37-38, 106, 138-39, 147, 168, 170, 171, 239-40, 245, 252, 255, 341, 342, 346, 354, 368, 370 (see also Model validity)

- Criticality 72-73, 160, 165, 168
 Criticality grid / criticality matrix 72-73
 Cumulated states 270, 516
 Cumulative damage 180, 345, 538
 Cumulative distribution function → Distribution funct.
 Cumulative failure rate → Compound failure rate
 Cumulative operating time 6, 12, 122, 126, 127, 181, 328-37, 344, 409 (see also Random cumul.op.time)
 Cumulative processes 537-39
 Customer documentation → User documentation
 Customer requirements/needs 19, 401-05, 407-09, 410
 Customer risk → Consumer risk
 Cut sets approach 59 (see also Minimal cut sets)
 Cuts / cut sets theorem 513, 518
 Cutting of states 229, 237, 293
 Cycle (regenerative process) 493, 494-95, 530
 Cycles to failure 345
- Damage** 11, 13, 15, 26, 72, 74-75, 85, 93-95, 99, 102, 104, 106, 107, 151, 152, 180, 345, 346, 363, 369, 371, 374, 395, 538 (see also Cause, Test, Visual)
 Damage evolution/accumulation 109, 345, 346
 Damp test → Humidity test
 Danger 11, 299
- Data**
 • analysis 35, 346-52, 353-68, 406, 489, 541-76, 585-87
 • collection 21, 22, 23, 313, 396, 426-28
 • retention 89, 97-98
- DC parameter 88, 92
 Death process 61-64, 167, 517
 (see also Birth and death process)
 Debug test 166
 Debugging 160, 166
 Decentralized logistic support 129-30, 133
 Decoupling device 32, 66, 148, 151 (see also Multiple failure mechanisms, Multiple failure modes)
 Decreasing failure rate 6-7, 349-50, 458, 460
 (see also Strictly increasing/decreasing failure rate)
 Decreasing intensity 357, 360-61
- Defect** 1, 3, 4, 7, 12-23, 72, 86, 97, 103, 109-11, 117, 159, 162-68, 363, 377, 388, 389-91, 394-99, 416
 (see also Potential, Dynamic, Nonconformity)
 • causes / examples 95, 102, 103, 106-07, 110, 150-53, 162-64, 363, 370-71, 374-75, 377-78
 • detection → Fault detection
 • localization/elimination hardware 311-84
 • localization/elimination software 166-68
 • prevention hardware 66, 72-80, 120, 144-59, 369-70, 371-73, 375-76, 407-25
 • prevention software 66, 72-80, 159-65, 407-25
- Defect freedom (software) 159, 162, 166
 (see also Fault tolerant)
- Defect tolerance (software) 159, 160, 162, 164, 165
 Defective probability p 12, 86, 311-20, 371, 374-75, 376-83, 551, 564
 Deferred cost 11, 12, 14, 376-83
 Definition of probability 431-34
 Definitions and terms used in RAMS engineering 2-15, 162, 385-400
- Deformation mechanisms/energy 109, 375
 Degradation 7, 66, 92, 96, 101, 112, 157, 395, 408
 (see also Graceful degradation)
 Degree of freedom 351-52, 446, 461, 573, 575, 578-80
 Delay 8, 112, 113, 242, 387, 394
 De Moivre - Laplace theorem 472, 556
 Demonstration (acceptance test)
 • availability 325-27, 409, 569-71
 • constant failure rate λ or $MTBF \equiv 1/\lambda$ 332-37, 408-09 (in particular 317, 335)
 • MTTR 339-40, 409
 • probability p , R , $PA=AA$ 314-20, 321-22, 564-68 (in particular 317, 335)
- De Morgan's laws 430
 Dendrites 95, 100
 Density 440, 446, 451
 Density rate → Failure rate
 Dependability 9, 11, 13, 388, 402, 403, 517
 Dependence between $MTTF_{Si}$ & $MTTF_{Sj}$ 512
 Derating 33, 79, 82, 84, 86, 144-45, 388
 Design FMEA/FMECA 72, 78, 390
 Design guidelines 13, 25-27, 66, 77, 79, 84, 412, 415
 • components/assemblies 150-53
 • cooling 145-47
 • derating 37, 144-45
 • EMC/ESD 148-49
 • ergonomic/human/safety aspects 158-59, 294
 • maintainability 154-159
 • moisture 85, 147 (see also Humidity test)
 • package form/type 147
 • reliability 144-54
 • software quality 159-68
 • temperature 37, 145-47
 • testability 155-57
 (see also Mandatory, Procedure, Rules)
- Design of experiment 71, 406
 Design reviews 13, 16, 21, 26, 27, 77, 79, 108, 120-21, 160, 164, 165, 377, 388, 412, 417-19, 421-25
 Design rules → Design guidelines, Rules
 Destructive analysis/test 92, 104, 105, 346
 Detection → Fault detection
 Deterministic → Defect, Systematic failure
 Device under test (DUT) 88
 Dew point 104
 Diagnosis 113, 115, 116, 120, 249
 (see also Fault localization)

- Diagram of transitions
- probabilities 61, 190, 197, 203, 215, 221, **235**, **503**, **504-06**, **507**, 509, 510, 517, 519
 - rates 204, **238**, 246, 247, **248**, 251, 253-58, 261, **263**, **267**, 272-73, 277,
 - states **194**, **208**, **223**, 252, 296-98, 303-05, 307, 309, 527, 528, 529
- Die-attach 93, 373
- Dielectric breakdown → Time **dep.** dielectric breakdown
- Difference between → Distinction between
- Difference equations **62-63**, **197**, **508**
- Different elements **44-45**, **202-03**, **232**, **233**
- Different required functions **29**, **30**, **259-71**
(see also Censoring, Phased-mission systems)
- Differential eqs. (method of) **63**, **173**, **197-99**, **507-10**
- Digital ICs **88-107**, **145**, 148-51, **372**, **591**
- Diodes **145**, 149, **150**, 151, **372**, **590**
- Directed connection/arc **31**, **55**, **275**, **287**
(see also Bi-directional)
- Disaster → Accident/disaster
- Discrete random variable **440**, 443, 445, **446**, **465-70**
- Discrimination ratio **315**, **326**, **334**, **335**
- Disjunctive normal form 59
- Dislocation climbing **109**, **375**
- Dispersion → Variance
- Disposal **13**, **19**, **391**
- Disregarding (ignoring) **88**, **133**, **294**, **296**, **297**, **298**, **354**, **363** (see also Negligible)
- Distinction between
- active & standby redundancy **43**, **62-64**, **201**, **202**, **213**, **217**, **217-18**
 - arrival times & interarrival times **480**, **533**
 - deterministic & random failure/faults **363**
 - early failure & systematic failure or defect **7**, **363**
 - failure & defect **3-4**, **7**, **117**, **363**, **388**, **389**, **391**
 - Markov & semi-Markov proc. **478**, **502**, **521**, **522**
 - memoryless & without aftereffect **355**, **489**, **532**
 - random variables & observations **542**
 - reliability & availability **9**, **170**, **386** & **397**, **508** & **509**
 - reliability & interval rel. **40**, **176** & **179**, **509** & **510**
 - reliability & safety **9**, **303**, **397** & **399**
 - renewal & regeneration point **480**, **491**, **494**
 - repairable & nonrepairable → Repairable versus nonrepairable
 - software and hardware quality assur. **159-60**, **161**
 - time & failure censoring
 - data analysis **332**, **553**, **558-60**
 - reconfigurable systems **259-71**
 - time-homogeneous & stationary **478-79**
 - MDT_S and $MTTR_S$ **121**, **124**, 200, 217, **279**, **394**
 - $MTBF_S$, $MTTF_S$, MUT_S **6**, 199-200, 217, 270, **279**, **392-94**, **515-16**
 - $MTTF_{Si}$ and $MTTF_{Sj}$ **512**, **519**
 - MUT_S and $\sum P_i MTTF_{Si}$ **279**, **516**
 - $P_{ij}(\delta t)$ and $Q_{ij}(\delta t)$ **503**, **523**
 - p_i and P_i **496** (footnote), **513**, **525**, **530**
 - $R(0)$ and $R(0 | x_0)$ **40**, **397**, **442**
 - $R(t)$ and $R(t | x_0)$ **40**, **397**, **442**
 - t_1^*, t_2^*, \dots and t_1, t_2, \dots **353**, **356**, **365**, **533**
 - $\lambda(t)$ and $f(t)$ **7**, **441-42**
 - $\lambda(t)$ and $h(t)$, $m(t)$ **7**, **356**, **364**, **390-91**, **482-83**, **532**, **540**
 - λ , λ_S , λ_{S0} **177**, **390**
 - $\lambda(t)$ and $z_S(t)$ **7**, **390-91**, **540**
 - $\tau_1^*, \tau_2^*, \dots$ and τ_1, τ_2, \dots **353**, **365**, **533**, **542**
- Distributed/meshed systems/structures **52**, **275-76**
- Distribution function **439**, **446-47**, **450**, **457-70**
• with random parameter **444**
- Distribution law **439**, **450**, **477**, **497**, **498-99**
- Documentation **7**, **13**, **15**, **19**, **115**, **116**, **118**, **154**, **156**, **158**, **159**, **161**, **162**, **163-64**, **369**, **387**, **413**, **417-19**
- Does not close/open **266**
(see also No connection, Stuck-at-state)
- Dominant failure mechanism/rate **36-38**, **64**, **109**, **257-58**, **343-44**, **373**, **375**
- Dormant state **33**, **35**, **145**
- Double one-sided sampling plan **319-20**
- Down, down state (d, \bar{U}) **57-58**, **61**, **173**, **176**, **277-78**, **490-91**, **507**, **524** (see also Up, up state)
- Down time **123-24**, **181**, **242**, **270**, **326-27**, **538**, **561**, **569** (see also System mean down time MDT_S)
- Drift **3**, **71**, **74-75**, **76**, **79**, **83**, **100**, **101**, **113**, **147**, **151**, **410**, **427**, **588-91** (see also Failure mode)
- Drivers **148**, **151**
- Drying material **147**
- Duane model **364-66**, **366-68**
- Duration (sojourn, stay) → Stay time
- Duty cycle **38**, **67**, **290**, **408**
- Dwell time **98**, **108**, **109**, **373**, **375**
- Dynamic burn-in **101**, **111**, **372-73** (see also Burn-in)
- Dynamic defect **3-4**, **159**, **367**, **388**, **398**, **399**, **416**
- Dynamic fault tree / gate **76**, **281-82**
- Dynamic gates **76**, **281**
- Dynamic parameter **88**, **150**, **370**
- Dynamic stress **69**, **149**
- Early failures **4**, **6-7**, **35**, **101**, **109**, **345**, **349-50**, **357**, **362**, **363**, **367**, **371**, **373**, **376**, **386**, **389**, **444**, **483-84**
- Early failures period **6-7**, **349-50**, **357**, **362**, **367**
- EBIC/EBT (el. beam ind. current / tester) **91**, **104**, **105**
- Ecological/Ecologically acceptable **10**, **406**, **407-08**
(see also Sustainable)
- EDF → Empirical distribution function
- Edges **275**
- EDX spectrometry **104**

- Effect (consequence) **4, 73, 427**
- common cause failures **42, 52, 66, 72, 79, 255, 271-74, 274, 277, 286, 397, 422**
 - imperfect switching **46, 47-48, 49, 62, 149, 220, 26, 243-47, 248, 257-58, 266-69, 282-85**
 - incomplete coverage **116-18, 249-55, 256**
 - series element **47, 72, 220-25, 226-28, 233, 274**
(see also Compromises, **Disregarding**, Negligible)
- Effectiveness → Cost effectiveness
- Efficiency (software) **162**
- Efficient estimates **549, 550**
- Electrical characterization **90, 91-93, 108**
- Electrical overstress **96, 153, 371**
- Electrical test
- assemblies **374-75**
 - components **88-92**
- Electromagnetic compatibility (EMC) **79, 82, 84, 108, 144, 148-49, 363, 421**
- Electromigration **6, 89, 95, 97, 103, 106, 345**
- Electron beam induced current (EBIC) **104**
- Electron beam tester **91, 104**
- Electronic assemblies
- accelerated test **343-44, 376**
 - design guidelines **151-53**
 - qualification test **108-11**
 - testing and screening **374-76**
- Electrostatic discharge (ESD) **89, 94, 102, 104, 106-07, 108, 144, 148-49, 153, 369, 371, 374**
- Elementary event **429-30**
- Elementary renewal theorem **485**
- Elements of a quality assurance system **13, 21**
- Elements which appear more than once in an RBD **29-30, 31, 32, 53, 54, 56, 69, 275-76, 284, 285, 289**
- Embedded
- Markov chain **170, 252, 278, 287, 291, 494, 496, 498, 501-03, 513, 514, 521-27, 530**
 - renewal process **176, 210-11, 478, 490-91, 494-95, 530**
 - semi-Markov process **171, 204, 223, 478, 494, 522, 526, 526-29, 530** (see also **Semi reg. proc.**)
- Embedded software **159, 164**
- EMC → Electromagnetic compatibility
- Emergency situation **158, 294**
- Emission microscopy (EMMI) **104**
- Empirical (see also Estimation)
- distribution function (EDF) **346-51, 542-47**
 - evaluation of data **346-51, 459, 542-48, 585-87**
 - failure rate **4-5**
 - mean value function **362**
 - mean/variance/moments **4, 327, 337-38, 544-45**
 - methods, **541-48**
 - reliability function **4-5**
- Empty set **429, 430**
- Environmental
- conditions/stress **28, 33, 36, 79, 81-84, 154, 392, 401, 406, 422**
 - stress screening (**ESS**) **6-7, 363, 375, 389, 398**
- Environmental and special tests
- assemblies **108-09**
 - components **89, 92-100**
- Epistemic uncertainties **300**
- EPROM/EEPROM **34, 96, 97, 98, 151, 372**
- Equations for Markov & semi-Markov models **172-73, 507-16, 523-26**
- Equivalence between asymptotic & stationary/steady-state **185-88, 488, 493, 495, 513, 514, 524, 525, 530**
- Equivalent events **430**
- Ergodic distribution **497, 513**
- Ergonomics **120, 158-59, 294, 411, 423, 425**
- Erlang distribution **193, 324, 326, 461, 531, 562, 570**
- Errare humanum est **158**
- Error **4, 7, 72, 76, 77, 78, 95, 158-59, 160, 163-64, 294-98, 303, 309, 363, 388, 390, 391** (see also **Flaw**, Human error, Misuse)
- Errors at start **168, 368** (see also **Refuse to start**)
- Error correcting code **66, 159, 164**
- Error effect/consequence (**human**) **294-98, 303, 308-10**
- ESD → Electrostatic discharge
- ESS → Environmental stress screening
- Estimate → Empirical, Parameter estimation
- Estimated reliability **3, 321-22**
- Estimation (statistical)
- availability **323-24, 327, 561-62**
 - failure rate λ (k fixed) **329, 553, 559-60**
 - failure rate λ or $MTBF \equiv 1/\lambda$ (T fixed) **328-32, 551, 553, 558-59** (in particular **331**)
 - HPP / Poisson distribution **552, 558**
 - MTTR **337-39**
 - NHPP **365-66, 536**
 - point **549-51**, interval **554** (basic theory)
 - probability $p, R, PA=AA$ **312-14, 321-24, 551, 554-58, 561-62** (in particular **313, 321, 324**)
- ETA → Event tree analysis
- Euler's integral **582**
- Events **429-30**
- independent **435**
 - mutually exclusive **435, 436**
- Event field **429**
- Event tree analysis (ETA) **76, 286, 294**
- Evolution of a Markov/semi-Markov process **292, 501-02, 522**
- Examples of real systems **30, 32, 68, 69, 235, 267, 275, 276, 285**
- Exchangeability **116, 157, 424**
- Expanding a 2-out-of-3 to a 1-out-of-3 red. **49, 592**
- Expected percentage of performance **271, 517**

- Expected percentage of time in Z_i (P_i) **514**, 525, 530
 Expected value **445**, **447**, **452**, **454** → Mean
 Exponential distribution **6**, **40**, 126, 240, 277-79, **328**, 390-91, **442-43**, **446-47**, **457-58**, 551, 553
 (see also Constant failure rate λ)
 External cause/event/influence **10**, **76**, **78**, 271, 280-81, **286**, **299-310**
 External initialization (test) **155**
 Extreme value distributions **459**
 Extrinsic **3-4**, **86**, **389**, **427**
 Eyring model **99**, 102, **109**, **345**
- F**
 Factorial ($n!$) **582**
 Fail-safe behavior/procedure **1**, **10**, **66**, **72**, **79**, **120**, **158-59**, **160**, **164**, **301-10**, **423**, **424**, **425**, 517
 Failure **1**, **3-4**, **6-7**, 22, **389**, **390**, 397 (see also Fault)
 Failure analysis **87**, **89**, **95**, **101**, **102-05**, **107**, **110**
 Failure cause **3-4**, **10**, **73**, **95**, **105**, **106-7**, **110**, **389**, **427**
 Failure censoring → Censoring
 Failure collection → Fault collection
 Failure coverage → Incomplete coverage
 Failure detection → Fault detection
 Failure effect → Fault effect
 Failure-free operating time **39**, **385** → Failure-free time
 Failure-free time **3-6**, **39-40**, **175**, **238-40**, **390**, **440-41**
 Failure frequency → System failure frequency
 Failure hypothesis **69-70**
 Failure intensity $z(t)$ **5**, **7**, **279**, 362, **389**, **482**, **537**, **540**
 • at system level $z_S(t)$ **279**, **537**, **540**
 Failure localization → Fault localization
 Failure mechanism **4**, **37**, **38**, **64-65**, 92, 96-100, **102-103**, **108**, **109**, **111**, **341-46**, **354**, 371-76, **389**, **444**
 Failure mode **3**, **25**, **27**, **29**, **42**, **62**, **66**, **72-76**, **101**, **245**, **257**, **266**, **277**, **389-90**, 415, **423**, **427**, 588-91
 • distribution **100**, 588-91
 • examples **51**, **64-65**, **100**, **248**, **257-58**, **266**, 588-91
 • investigation **64-65**, **72-78**, **245-48**, **257-58**, **266-69**
 Failure modes analysis → FMEA / FMECA
 Failure propagation → Secondary failures
 Failure rate λ , $\lambda(t)$, $\lambda(x)$ **4-7**, **32-38**, **39**, 109, **170**, 356, **390-91**, **441-43**, 457-69, **482**, **532**, **540**
 • analyses **25-67**, **415**
 • confidence limits **330-32**, **558-61** (in particular **331**)
 • demonstration **332-37** (in particular **335**)
 • distinction to → Distinction between
 • dormant/standby **33**, **35**, **43**, **62**, **145**
 • estimation **330-32**, **551**, **553**, **558-60**
 • for common causes **274**
 • handbooks **35-36**
 • models/modeling → Model
 • of mixed distributions **40**, **344**, **350**, 444
 • of nonrepairable items **5**, **39**, **390-91**, **441-42**
 • of repairable items **5**, **390-91**, **442**
 • of series systems **31**, **42**, **190**
 • of 1-out-of-2 redundancy **43**, **199**
 • temperature dependence **3**, **34**, **36-37**, **341-46**
 • values 36, 38, 50, 341, 408, 588-91
 (see also Compound, Conditional, Constant)
 Failure recognition → Fault detection
 Failure severity **72-73**
 Failure tolerant → Fault tolerant/reconfigurable **struct.**
 Failures with constant failure rate λ **6-7**, **35**, **239**, **363**
 False alarm **66**, **249**, **255** (see also Alarm)
 Fatigue **3**, **6**, **83**, **98**, **101**, **103**, **345**, **459**, **590**
 (see also Coffin-Manson, Wear-out)
 Fault **4**, **23**, **66**, **72**, **73**, **76**, **78**, **80**, **91**, **101**, **113**, **116**, **117**, **120**, **159**, **249**, **391** (see also Defect, Failure)
 Fault collection **21**, **22**, **23**, **369**, **426-28**
 Fault coverage **117**, **249** → Incomplete coverage
 Fault criteria **425** (see also Fault effect)
 Fault detection **74**, **79**, **90**, 102, 105, **112-13**, **116-19**, **120**, **154-59**, **171**, **240-41**, 249, 274, 277, **387**, **395**, 421-23 (see also Defect, Fault tolerant)
 Fault effect/consequence **4**, **10**, **67**, **72-80**, **101**, **294-98**, **389-90**, **399**, 423, 425, **427** (see also Effect, Error, ETA, FMEA/FMECA, FTA, Negligible)
 Fault localization **112-13**, **116-19**, **154-59**, **249-56**, **374**
 Fault models/modeling **90-91**, **243-58**, **266-74**, **368**
 Fault modes and effects analysis **72** → FMEA
 Fault review board **427**, **428**
 Fault sensing device **73**
 Fault tolerant/reconfigurable structures **49**, 64-65, **66**, **101**, 159, **160**, 164-65, **255**, **259-71**, **274**, 275-76, 299-310 (see also Defect, Mandatory, Redundancy)
 Fault tree/Fault tree analysis **66**, **76**, **78**, **280-85**, **391**
 Fault tree structure function ($\phi_{FT}(\xi_1, \dots, \xi_n)$) **283-85**
 Favored (can be) → Realize an advantage
 Feasibility/feasibility check **11**, **19**, **77**, **121**, **161**, **388**, **417**, **419**, **421**, **422**
 Feedback **22**, **86**, **87**, **104**, **150**, **155**, **158**, **160**, **161**
 Fiber optic **149**, 157
 Field data **3**, **26**, **35-37**, **51**, **79**, **86**, 353-62, **426**
 Field data change service **118**
 Field of events → Event field
 Field operation **14**, **82**, **83**, **92**, **99**, **341**, **371**
 Figures → Numerical
 Final value theorem **583**
 Fine leak test **373-74**
 Finite element analysis **69**
 Firing rule **287**
 First delivery **384**
 First-in / first-out **153**, **226**, 235, 239, **263**, **504**, **506**
 First production item 417 (see also Pilot production)
 Fishbone diagram → Ishikawa diagram
 Fisher / F-distribution 324-27, 467, **550**, 556, 561-62, 569-71, **580-81**

- FIT (Failures in time) **36, 38, 80, 588-91**
 Fit of models **99, 102, 356** (see also **Model validity**)
 Fitness for use **11, 395** → **Quality**
 Fix replacement **134-35, 136, 138**
 Fixed length test → **Simple two-sided test**
 Flaw **26, 106-11, 294, 363, 375** (see also **Error**)
 Flexibility (software) **162**
 Flow of failures/events **168, 328, 330, 353, 364, 536**
 FMEA/FMECA **13, 15, 17, 27, 29, 42, 66, 69, 72-75, 78, 79, 117, 120, 160, 244, 250, 255, 259, 266, 274, 277, 301, 310, 389-90, 398, 410** (see also **Mandatory**)
 Force of mortality **5, 391, 442** → **Failure rate**
 Formation → **Motivation and training**
 Forward equation → **Kolmogorov equation**
 Forward recurrence time **181-82, 185, 188, 484-85, 486, 489, 491-92** (see also **Rest waiting time**)
 FRACAS → **Quality data reporting system**
 Fractile → **Quantile**
 Fraction of defective items → **Defective probability**
 Frequency/duration **270, 514-17**
 Frequency of
 - events **481** (RP), **489** (HPP), **532** (NHPP)
 - external events **286, 303-09**
 - failures/repairs **279 & 515-16** (MP), **525** (SMP)
 - state Z_i **525** (SMP), **526** (MP), **530** (RGP)
 FTA → **Fault Tree Analysis**
 Function of a random variable **444, 464**
 Functional block diagram **29, 30, 32, 68, 230, 235, 244, 267, 282**
 Functional test **88, 90-92, 374**
 Functionality **8, 51, 82, 112, 113, 162**

Gain → **Improvement**
 Gamma distribution **126, 187, 342, 446-47, 460-61**
 Gamma function **460, 582** → **Complete, Incomplete**
 Gate review **165** → **Design review**
 Gaussian distribution → **Normal distribution**
General/arbitrary point process (GPP) **168, 353, 539-40**
 General reliability data analysis **353-68**
 Generalized cut sets theorem **513, 518**
 Generalized Eyring model **345**
 Generating function → **Moment generating function**
 Generation of nonhomogeneous Poisson proc. **536**
Generator for rare events **292**
 Generator for stochastic jump processes **291-92**
 Genuine acceleration **341**
 Geometric distribution **292, 446-47, 469**
 Geometric probability **433**
 Glass transition temperature **85**
 Glassivation → **Passivation**
 Glitches **151**
 Glivenko-Cantelli theorem **543**
 Go/no go circuitries/decisions **158 / 428**

 Gold-plated pins **94, 153**
 gold wires **100**
 Good-as-new → **As-good-as-new**
 Goodness-of-fit tests **346-52, 356, 366, 571-76**
GPP → **General point process**
 Graceful degradation **66, 259, 266-71, 277**
 Gradual failure **4, 427**
 Grain boundary sliding **109, 375**
 Graphical evaluation/approach **347-48, 351, 357, 361-62, 545-48**
 Gross leak test **373-74**
 Ground **148-49, 150, 151, 152, 157**
 Ground tracks **151**
 Growth → **Quality growth (software), Reliability growth (hardware)**
 Guard rings **149, 151**
 Guidelines → **Design guidelines**

Halogen-free **153, 589**
 HALT → **Highly accelerated life test**
 Handbooks **20, 21, 35, 36, 118, 413, 417, 428**
 Handling **4, 82, 84, 85, 94, 151, 363, 378, 399, 417**
 Harm **15, 299, 310, 395, 398, 399**
Harmonization → **Standardization**
 HASL → **Hot air solder leveling**
 HASS → **Highly accelerated stress screening**
 HAST → **Highly accelerated stress test**
 Hazard rate → **Failure rate**
 Hazards **5, 9, 299, 300, 310, 391, 399, 404, 442**
 HBM → **Human body model**
 HCMOS **148, 149, 591**
 Heat sink **146**
 Hermetic enclosure/container **147, 153**
 Hermetic package **85, 104, 147, 371-74**
 Heuristic methods **52-57, 353-54, 356, 361-62, 483-84**
 Hidden faults (failures, defects) **8, 14, 66, 79, 107, 112, 113, 116, 117, 120, 154, 156, 240, 249-56, 389, 395**
 High temperature storage **89, 98, 371, 372**
 Higher-order moments **448, 449, 545**
 Highly accelerated life test (HALT) **346**
 Highly accelerated stress screening (HASS) **370**
 Highly accelerated stress tests (HAST) **98, 99, 346**
 Historical development **16, 17, 85, 405-06**
 History of reliability → **Story of reliability**
 Homogeneous → **Time-homogeneous**
 Homogeneous Poisson process → **Poisson process**
 Hot air solder leveling **153**
 Hot carriers **89, 96, 102, 103**
 Hot redundancy → **Active redundancy**
 HPP → **Homogeneous Poisson process**
 Human aspects/factors **2, 3, 9, 10, 13, 18, 27, 77, 120, 158-59, 165, 294-98, 397, 399, 411, 412, 423, 425**
 Human body model (HBM) **94**

- Human errors **10, 119, 158-59, 163, 294-95, 300-03, 308-09** (see also **Error, Flaw, Misuse**)
- Human reliability **16, 174, 294-98** (see also Risk management)
- Humidity tests **89, 98-100** (see also **HAST, Moisture**)
- Hypergeometric distribution **446-47, 470**
- Hypotheses
- failure **69, 70**
 - statistical **314-16, 321-22, 325, 332-33, 335, 339, 346-52, 357-61, 563-64, 566-76**
- Idempotent law 430**
- Imbedded → Embedded
- Imperfect switching **243-48, 257-58** → Effect
- Importance measures (IMs) **300**
- Impossible event **430** (see also Empty set ϕ)
- Improvement through
- preventive maintenance **134-41, 240-42, 243, 250**
 - redundancy e.g. **43 versus 40, 202, 217 v. 201**
 - repair e.g. **217 versus 47, 227 v. 44, 233 v. 232**
- Impulse $\delta(t)$ **584**
- In-circuit test **374**
- In-process tests **370, 412**
- In steady-state → Stationary
- Inclusion/exclusion principle **438**
- Incoming inspection **21, 90, 150, 370, 377, 378, 379-83, 396, 411, 420, 423**
- Incomplete coverage **116-18, 249-56**
- Incomplete Gamma function **460, 582**
- Incomplete human performance **294-98, 393, 309**
- Increasing failure rate **6-7, 134-40, 240-43, 442, 443, 447, 458, 460, 483-84** (see also Strictly)
- Increasing intensity **357-60**
- Independent
- elements **41-51, 52, 220-37** (see also Totally ind.)
 - events **435, 436, 437**
 - increments **355, 368, 477-78, 489, 532, 536, 540**
 - random variables **451, 453, 454, 454-56, 461, 463, 472, 477, 502, 542**
 - stress/strength **70-71**
- Indicative values → Numerical**
- Indicator **56, 58, 61, 179, 327** (see also Binary process)
- Indices **3, 39, 169, 173, 175, 279, 394, 507, 512**
- Indirect plug connectors **120, 157**
- Induced failure/failure mechanism **83, 345**
- Inductive/capacitive coupling **91, 148, 151**
- Industrial applications (environment) **35-38, 83, 144-47**
- Influence of
- common cause failures/events → Common cause
 - failure mode **243-58, 266-69**
 - number of repair crews **141, 217-18, 232-33, 240**
 - preventive maintenance **134-40, 240-43**
 - repair priority **141, 220**
 - repair time distrib. **114-15, 133, 174, 206-07, 220**
 - series element **46, 47-48, 221, 225, 226, 227-28**
 - switch **243-47, 248, 257-58**
 - travel time **203-04, 527-28**
- Information feedback **22, 86, 104, 150, 396, 413, 428**
- Infrared soldering 153**
- Infrared thermography (IRT) **104**
- Inherent → Intrinsic
- Initial conditions/distribution **63, 187, 197, 198-99, 201, 215, 487, 493, 497, 498, 513, 523-26**
- Initial value theorem **583**
- Initiating event **286**
- Input/output pins/driver **150, 151** (see also CMOS)
- Inserted components **84, 109, 110, 111, 152**
- Inspection → Incoming inspection
- Instantaneous availability → Point availability
- Instantaneous failure rate → Failure rate
- Instantaneous reward rate → Reward rate
- Integral equations (method of) **172, 178, 200-01, 204-05, 208-12, 218-19, 223-25, 511-12, 523-24**
- Integral Laplace theorem **472, 556**
- Integrated circuits (ICs) **34-38, 84-85, 87-101, 145, 147, 150, 153, 344, 370, 371-74, 377-78, 591**
- Integrity (software) **162, 289, 426**
- Intensity (see also Renewal density)
- failure intensity **7, 356, 362, 389, 391, 516, 537, 540**
 - of a point process **540**
 - of a Poisson process **328, 330, 355, 357-61, 364, 365-68, 489, 519, 532, 533-35**
- Interactions **66, 79, 159-60, 163, 165, 290**
- Interarrival times **5, 41, 113, 175, 328, 353, 357, 362, 364, 368, 392, 442, 480, 483, 533, 535, 536, 540**
- Interchangeability **8, 157, 425** (see also Obsolescence)
- Interface **19, 66, 78, 79, 116, 363, 417, 419, 421-25**
- Al/Au, Al/Si, Si/SiO₂ **96, 97, 103**
 - hardware-hardware **66, 82, 118, 144, 151, 363**
 - hardware-software, man-machine, between documents **16, 299, 363, 418-20, 421-25**
 - software-software **161, 163, 164, 289, 424**
- Interference **26, 79, 82, 363, 421, 422**
- Intermetallic compound / layer **100, 103, 109, 153**
- Intermittent operation **85, 147**
- Internal visual inspection **89, 93, 104**
- Intersection of events **430**
- Interval estimate at system level (λ_s) **332**
- Interval estimation **554, 554-58** (in particular **313, 324, 331**)
- failure rate λ **330-32, 558-60**
 - lognormal distribution parameters **338-39**
 - number of observations **473-74, 558**
 - number of trials **475**
 - point availability **324, 327, 562**
 - unknown probability p **312-14, 321, 554-58**

- Interval reliability **40, 172-73, 179, 183, 184, 188, 195, 201, 205, 213, 216, 217, 278, 397, 492, 510, 524**
- Intrinsic or inherent availability/cause/failure/maintainability/reliability/weaknesses **3-4, 9, 11, 13, 23, 74-75, 86, 144, 172-73, 300, 301, 302, 310, 368, 389, 395, 427**
- Inverse function **291, 444, 464**
- Ion migration **103**
- Irreducible Markov chain/process **172-73, 278, 494, 497, 513-14, 518, 522, 524, 525, 526, 530**
- IRT → Infrared thermography
- Ishikawa diagram **76-77, 78**
- ISO 9000: 2020 family **11, 402, 403**
- Item **2, 391**
- Jelinski-Moranda model 167**
- Joint availability **181-82, 183, 184, 188, 327**
- Joint density/distribution **450-51, 533, 535**
- Jump processes **498, 500, 511, 521-22, 530**
- Junction temperature **32-34, 79, 85, 145-47, 150, 342**
- Just-in-time **153**
- k -out-of- n : $G \rightarrow k$ -out-of- n redundancy**
- k -out-of- n consecutive → Consecutive
- k -out-of- n redundancy **31, 44, 61-64, 130-34, 213-16, 217, 218-19, 232, 233, 505, 517-20, 527, 529**
- k -terminal **275**
- Kepner-Tregoe **76, 78**
- Key item method **52-53, 54-56, 60, 68-69, 275-76, 284**
- Key renewal theorem **185, 186, 486, 493, 495**
- Kindness (test pattern) **91**
- Kirkendall voids **100**
- Kolmogorov backward/forward equations **500**
- Kolmogorov-Smirnov test **346-51, 356, 366, 536, 545-47, 572, 574-75, 581** (theorem **545-46**)
- Korolyuk theorem **531**
- k th moment / k th central moment **448**
- Lack in the diagnosis 90, 117, 168, 249, 300, 301**
- Lack of information 117, 168, 300, 301, 402**
- Lagrange multiplier **67**
- Laplace test **358, 360**
- Laplace transform **63, 198, 199, 455, 460, 512, 583-84**
- Large complex repairable systems **277-79, 293-94**
- Large series-parallel structures **31, 45-46, 226-37, 240**
- Last repairable unit → Line replaceable unit
- Last replaceable unit → Line replaceable unit
- Latch-up **89, 96, 103, 150, 153**
- Latent damage → Damage, Potential rel. problem
- Latent failure → Damage, Hidden failure
- Latent fault time → Undetected fault time
- Law of large numbers **471-72**
- LCC → Life cycle cost
- Lead-free solder **109, 111, 152, 375**
- Leadless **152**
- Leak test → Seal test
- Learning process/phase **150, 321, 363-64, 369**
- Level I, II, III **318**
- Liability → Product liability
- Life cycle cost (LCC) **11, 13, 16, 112, 387, 388, 391, 400, 407, 408, 415, 421**
- Life-cycle phases **19** (hardware), **161** (software)
- Life time **346, 353, 392, 400, 439, 585**
- Lightly loaded redundancy → Warm redundancy
- Like new → As-good-as-new
- Likelihood function → Maximum likelihood function
- Limit of models → Model validity
- Limit theorems of probability theory **470-75**
- Limited useful life **13, 35, 39, 79, 81, 85, 113, 116, 119, 120, 125, 146, 147, 150, 151, 177, 400, 589, 590**
- Limiting distribution/state probability **495, 513, 514, 518, 525, 530** (see also Asymptotic)
- Limits of the Boolean function method **57-61, 280**
- Lindeberg conditions **473**
- Line repairable unit → Line replaceable unit
- Line replaceable unit (LRU) **115, 116, 117, 119, 120, 125, 154, 157, 399**
- Linear/analog ICs/circuits **145, 148, 149, 155, 372, 591**
- Link → Edge
- Liquid crystals **104**
- List of preferred parts (LPP) → Qualified part list
- Load capability **33**
- Load sharing **26, 43, 44, 45, 52, 62, 61-64, 196-201, 214-17, 239, 277, 507-10, 517-19, 527, 528, 529**
- Localization → Fault localization
- Logarithmic Poisson model **367**
- Logistic delay **8, 113, 241, 242, 387, 394**
- Logistic support **2, 8, 9, 12, 13, 16, 18, 19, 21, 26, 114, 115, 118, 119, 121, 125, 129, 134, 143, 154, 160, 165, 171, 239, 242, 260, 387, 388, 392, 394, 399, 401, 408, 413, 419, 425**
- Lognormal distribution **37, 113-14, 193, 207, 337-40, 342, 351, 446-47, 463-64, 585**
- Lognormal probability chart **351, 585**
- Long-term behavior/stability **86, 101**
- Loss of image **376**
- Loss of performance **66, 72, 259, 267-70, 389, 400, 514**
- Lot tolerance percent defective (LTPD) **318-19, 568**
- Low occurrence 489, 537, 539**
- Lower bound ($PA(t)$, PA , R) **187, 260, 264, 265, 327** (see also Interval estimation)
- Lower confidence limit → Confidence limits
- Lowest replaceable unit → Line replaceable unit
- LRU → Line replaceable unit
- LTPD → Lot tolerance percent defective**

- Machine model (MM)** 94
- Macro-structures (*MS*) 174, **199**, **229**, **233**, 234, 237, 269
- Maintainability 1, 8, 9, **13**, **113-15**, 162, **392**, 403
- analysis 72, **121-125**, **410-11**, **415**
 - **design** guidelines **154-59**
 - engineering **13**
 - estimation / demonstration / test **120**, **337-40**, **409**
 - software **162**
- Maintenance 8, **112-13** (see also **Preventive, Corr.**)
- concept 8, 112, **115-20**, **154**
 - cost **134-43**, **538**
 - levels **119-20**
 - strategy 35, 125, **134-41**, **240-56**, 257-74, **443**
- Majority redundancy 31, **49**, **66**, **158**, **164**, **218-19**, **222-25**, **233**, **249**, **254**, **295**
- Man-machine 16, **120**, **158**, **423** (see also **Ergonomics**)
- Mandatory for (see also **Conditions**, **Model validity**)
- accelerated tests **341**, **346**
 - as-good-as-new **386** (see also **Regeneration state**)
 - common cause failures (to avoid) **274**
 - component's selection **84-86**
 - data analysis **353-54**
 - elements appearing more than once in a reliability block diagram **30** (see e.g. 31, 32, 56, 69)
 - fault tolerant / fail-safe behavior **66**, **72**, **158-59**, **164**, **259**, **274**, **310**
 - FMEA/FMECA, **FTA and similar tools** 77
 - general data analysis **354**
 - human reliability **158-59**, **295**, **310**
 - incomplete coverage **249**, **254**, **255**
 - Markov processes 171, 277, **496**, **498**, **503**, 526
 - Memoryless property **40**, **443**, **458**
 - *MTBF* **6**, **40**, **328**, **392-93**
 - *MTTF_{Si}* **40-41**, **393**
 - Poisson processes (HPP & NHPP) **488**, **532**, **536**
 - quality & rel. (RAMS) assurance **17-21**, **407-25**
 - reconfiguration **66**, **116-18**, **164**, **259**, **266**, **274**
 - redundancy **27**, **42**, **66**, **72**, **164**, **239**, **255**, **274**, **397**
 - regeneration state / regenerative proc. **171**, **386**, **494**
 - reliability block diagram **29**, **30**
 - reliability growth **168**, **363**, **368**
 - reliability improvement **26-27**, **42**, **66**, **78**
(see also **Design guidelines**, **Design reviews**, **Rules**)
 - repairable systems **240**, **540** (see also **As-good-as-new**)
 - risk management **11**, **300**, **301**, **310**
 - semiconductor devices **148-50**
 - semi-Markov processes **521**, **522**
 - semi-regenerative processes **171**, **386**, **494**, **530**
 - short-term tests (HALT, HAST, step-stress) **346**
 - SMT **109**, **375**
 - software quality **159-66**
 - test hardware & software **116-18** & **166**
 - p_{ii} **496-97**, **500**, **522**, **526**
- Manson → Coffin-Manson
- Manuals/HDBKs **20**, **21**, **35-38**, **118**, **413**, **417**
- Manufacturability 79, 417, 421, **424**, **425**
- Manufacturing process 106-11, **152-53**, 369-84, **416**
- Manufacturing quality 16, 20, **86**, **369-84**
- Margin voltage 98
- Marginal density/distribution function **451**, **533**
- Marked point processes **531**
- Market / market needs **19**, 387, 396, **402**, **407**, **410**, **419**, **421**, **422**, **425** (see also **Time to market**)
- Marking 287
- Markov chain **496-97** (see also **Embedded MC**)
- Markov model **61-64**, 129-33, **141**, 167, **171**, **172-73**, **183**, 189-91, **196-204**, **214-18**, **220-21**, 225-28, 230-37, **240**, 245-48, 251-74, **277-79**, 294, **503**
- Markov processes (**MP**, finite nr of states) **498-521**
- basic characteristics **478**, **498-503**, **512-17**, **522**
 - irreducible **513**
 - mandatory for 171, 277, **496**, **498**, **503**, 526
 - simulation **291-93**
 - stationary **512**
 - time evolution **501-02**
 - time homogeneous **7**, **170**, **173**, **239**, **277**, **478**, **498**, **500-03**, **517**, **522**, **526**
- Markov property **478**, **498** (see also **Memoryless**)
- Markov renewal processes **521**
- Markov sequence **536**
- Markov theorem **497**, **513**
- Match/Matching **149**, **151**
- Mathematical statistics **541**, **541-76**
- Mature (stable) **32**, **38**, **96**, **98**, **153**, **154**, **371**, **374**
- Maximum (τ_{\max}) **456**
- Maximum acceptable p , \overline{PA} , λ **315**, **325**, **333**
- Maximum likelihood function / method **312**, **323**, **327**, **330**, **338**, **353**, **356**, **365-66**, **550-53**, **575**
- MC → Markov chain
- MDT_S **394** → System mean down time
- Mean (expected value) **6**, 39-40, **277-79**, **445**, **447**, **448**, **452-53**, **454**, **514-16**, 538-39, **544-45**
- accumulated reward **271**, **279**, **517**
 - down/up time MDT_S , MUT_S **123**, **124**, **191**, **173**, **200**, **237**, **242**, **270**, **278-79**, **394**, **515-16**, **525**
 - expected failures per year **270**, **408**
 - instantaneous reward rate **271**, **279**, **517**
 - logistic delay (MLD) **242**
 - number of failures/repairs for **Markov models** **278-79**, **515-16** (**525** for **SMP**, **540** for **GPP**)
 - operating time between failures *MTBF* **6**, **40**, **328**, **392-93**
 - estimation / demonstration **328-37**, **408-09**
 - $MTBF \equiv 1/\lambda$ **6**, **40**, **328**, **392-93**, **404**
 - *MTBF* versus *MTTF*, *MUT* **6**, **40**, **199-200**, **217**, **270**, **279**, **392-94**, **515-16**

- sojourn time T_i in Z_i **173**, 251, **523**, **526**, **530**
- survival failure-free time at age x_0 **442**
- time T_{ii} between successive occurrence of Z_i **525**, **526**, **530**
- time to failure ($MTTF$, $MTTF_{S_i}$) **6**, **39**, **41**, **63**, **172-73**, **176**, **277-79**, **393**, **512**, **524**
(in particular **201**, **213**, **217**, **227**, **232**, **233**)
with preventive maintenance **241**
- time to perform a preventive maintenance ($MTTPM$) **8**, **113**, **121**, **125**, **393**
- time to repair/restoration ($MTTR$) **8**, **9**, **113**, **121-24**, **394**, **490**
estimation / demonstration **337-40**, **409**
- time to restoration → Mean time to repair
- time to system failure → Mean time to failure
- undetected (latent) fault time τ_{UFT} 251, **443**
- up time → Mean down/up time
(see also Dependence, Distinction)
- Mean value function **355**, **362**, **364**, **367-68**, **532**, **540**
• at system level $Z_S(t)$ **537**
- Mean value theorem **495**
- Mechanical fatigue → Fatigue
- Mechanical keying/fixing **152**, **155**, **157**
- Mechanical reliability **68-71**, **73**
- Mechanical stress **69-71**, **83**, **98**
- Mechanism → Failure mechanism
- Median **114**, **450**
- Memories **90-91**, **95**, **97-98**, **151**
- Memoryless **354**, **355**, **477**, **489**, **523**, **532**, **533**, **536**, **540**
(see also Distinction, Without aftereffect)
- Memoryless property **7**, **40**, **62**, **179**, **197**, **200**, **220**, **241**, **295**, **302**, **329**, **332**, **390**, **443**, **447**, **458**, **469**, **478**, **489**, **491**, **498**, **501-03**, **507**, **510**, **511**, **553**, **558**
- Meniscograph method **94**
- Merging → State space reduction
- Meshed → Distributed
- Metal migration **100**, **103** (see also Electromigration)
- Metallization **95**, **97**, **98**, **100**, **103**, **104**, **154**, **373**
- Metallographic investigation **95**, **104**, **105**, **107**, **108-11**
- Method of
 - Boolean function **57-61**
 - differential equations **63**, **173**, **197-99**, **507-10**
 - integral eqs. **172**, 200-01, 204-05, **511-12**, **524**
 - key item **52-53**, 54-56, 60, 68-69, 275-76, 284
- Metrics (software quality) **160**
- Microcracks → Cracks
- Microsections **95**, **104**, **105**, **107**, **109-11**
- Microvoids **109**
- Miner's hypothesis **345**, **346**
- Minimal cut sets **59**, **60**, **76**, 275, 281, 283, 516
- Minimal operating state → Critical operating states
- Minimal path sets **58**, **60**, **76**, 275, 281, 283
- Minimal repair **138-39**, **387**, **443**, **535-36**
- Minimum (τ_{\min}) **456**
- Minimum acceptable *MTBF* **408**
- Mishandling → Misuse
- Misleading probability **295**
- Mission availability **9**, **140**, **180**, **183**, **260**
- Mission profile **3**, **28**, **38**, 68, 69, **79**, **392**, 409, 421, 425
- Mission reliability → Interval reliability
- Misuse (components / tools) **4**, **102**, **103**, **120**, **106**, **271**, **357**, **405**, **427**, **511**, **516** (see also Error)
- Misuse (terms) **6**, **40**, **179**, **393**, **397**, **540**
- Mitigate **9**, **72**, **73**, **74-75**, **78**, **153**, **286**, **299**, **300**, **301**, **310**, **395**, **398**, **399** (see also Check strategy)
 - incomplete coverage **255**
- Mixture of distributions **7**, **40**, **71**, **350**, **444**, **547**
- MLD* → Mean logistic delay
- MM → Machine model
- Modal value **113-14**, **450**
- Mode → Failure mode
- Model **406**
 - for cost optimization → Cost optimization
 - for early failures/wear-out period **7**, **349-50**, **367**, **444**, 459, 460, 483-84
 - for failure rates/mechanisms **35-38**, **94-100**, **102**, **103**, **109**, **341-46**, **444** (see also Multiple f. m.)
 - for faults → Fault models
 - for human aspects **294-98**
 - for quality growth (software) **166-68**
 - for reliability growth (hardware) **363-68**
 - for risk/safety analysis/management **300-10**
 - validity/verification **26**, **52**, **71**, **102**, **109**, **117**, **168**, 170-71, **174**, **220**, **238-40**, 249, **252**, **260**, **277-79**, **280**, **295**, **300**, **302**, **342**, **346**, **353-54**, **356**, **357**, **362**, **363-65**, **368**, **406**, **483**, **503**, **536**
(see also Assumptions, Mandatory)
- Modification **21**, **119**, **162**, 163, 165, **363**, **369**, **387**, **412**, **418** (see also Changes)
- Modified renewal process **480**
- Module/Modular
 - hardware **116**, **120**, **154-55**
 - software 161, **163**, **164**, **166**
- Moisture **85**, **93**, **98-99**, **147**
- Moment generating function 538, **583**
- Monotonic trend (test for) **357-62**
- Monte Carlo **280**, **290-92**, **294**, **464**, **473**, **475**, **532**, **536**
- Moranda-Jelinski model **167**
- More than one failure mechanism/mode → Multiple
- More than one repair crew **204**, **217-18**, **231**, **232**, **239**, **240**, **276**, **280-85**, **293-94**, **504**, **505**, **517-21**, **531-32**
(see also Totally independent elements)
- More than 2 states → Multiple failure modes/mech.
- Motivation/training/training level **18**, **21**, **24**, **115**, **119**, **154**, **159**, **294**, **310**, **413**, **423**
- MP → Markov process

- MS* → Macro-structures
MTBF → Mean operating time between failures
MTBF $\equiv 1/\lambda$ 6, 40, 328, 392-93, 404
MTBF versus *MTTF*, *MUT* 6, 199-200, 217, 270, 278-79, 392-94, 515-16
MTBF_S 6, 393, 394
MTBUR (mean time between unsched. removals) 393
MTTA (mean time to accident) 299, 301-09, 393
MTTF → Mean time to failure
MTTPM → Mean time to perform a preventive maint.
MTTR → Mean time to repair/restoration
MTTR_S (mean of all repair/restoration times) 121-24
 Multi-states → Multiple
 Multidimensional random variable → Random vector
 Multifunction system → Phased-mission system
 Multilayer 97, 110, 148, 154
 Multimodal 450
 Multinomial distribution 352, 467, 575, 576
 Multiple failure mechanisms 37, 64-65, 102, 271, 343-44, 354, 444 (see also Compound failure rate)
 Multiple failure modes 37, 52, 64-65, 66, 248, 255, 257-58, 266-69, 275 (see also Common cause)
 Multiple fault/consequences 76, 271, 274, 391, 444
 Multiple one-sided sampling plans 319-20
 Multiplication theorem 436-37
 Multi point ground 149
MUT_S 394 → System mean up time
 Mutually exclusive events 57, 64, 65, 178, 244, 430, 431-32, 435, 436, 437, 438 (see also Pairwise)
 Mutually independent 435, 451 → Independent
 MUX 155, 156
- Nanocoating** 147
n-dimensional distribution function 450, 476 (see also Random vector)
 N-modular redundancy 49
 N-self configuring programming (NSCP) 66, 164
 N-version programming (NVP/NVS) 49, 66, 164
 NBTI (negative bias temperature instability) 103
 Negligible (can be neglected)
 - alarm circuitry 298
 - common cause failure 273-74
 - external event 304-10
 - human error 296, 297, 298, 303, 309
 - imperfect switching 245, 246, 247, 248, 257-58
 - incomplete coverage 253-54, 255, 256
 - repair times distribution shape 206-07, 220
 - series element to a redundancy 46, 221, 225, 226 (see also Influence of)
- Network reliability 275-76
 New-better-than-used / New-worse-than-used 443
 NHPP → Nonhomogeneous Poisson process
 No aging 443 (see also Constant failure rate)
 No connection 246, 248, 257-58, 266-69
no FF (no further failures at system down) 170, 229 239 (see also Only one repair crew)
 No start at call 252 (see also Refuse to start)
 Nodes 275-76
 Non-irreducible Markov chain 513
 Non-Markovian 277, 279
 Non-parametric 545, 563
 Non-qualified parts 150 (see also Qualified part list)
 Nonconformity 1, 388, 394
 Nondestructive analysis 104, 105
 Nonelectronic components 35
 Nonhermetic packages → Plastic package
 Nonhomogeneous Poisson processes → Poisson proc.
 Nonregenerative stochastic processes 170, 171, 193, 207, 219, 478, 494, 526, 531-40
 Nonrepairable item (up to system failure) 5-7, 39-60, 61-71, 243-44, 275-76, 283-85, 390, 393
 Nonvolatile memory 87, 97-98, 151
 Normal distribution 37, 70, 342, 446-47, 462-63, 464, 472-75, 487, 544, 550, 556-57, 577, 587
 Normal probability chart 587
 Normal process 479
 Normal/reduced/tightened test 318
 Not regeneration state 208, 211, 218, 223, 527, 528, 529
 Null hypothesis (H_0) 314, 325, 332, 339, 346, 563-64
 Number of defects at $t=0$ 167, 168, 368
 Number of observations 314, 473, 543, 555-56, 573
 Number of spare parts 127, 128, 130-33, 413
 Number of states 56, 65, 166, 196, 226, 235, 506
 Number of trials 291, 314, 431, 434, 465-69, 473-75
 Numerical
 - computation 289-92
 - examples 50-51, 70, 207, 237, 264-65, 269, 270, 322, 344, 347-52, 473-75, 483-84, 574
 - test conditions 83, 89, 94, 98-100, 108-09, 371-76
 - values for derating 145
 - values for failure modes 100, 588-90
 - values for failure rates 7, 36-38, 50-51, 408, 588-91
 - values for defective probability 371, 374-75
- OBIC** (optical beam induced current) 104, 105
OBIRCH (optical beam induced resistivity change) 106
 Object oriented programming 164
 Observability 155
 Obsolescence 8, 79, 116, 143, 150, 392, 400, 416, 423
 OC → Operating characteristic curve
 Occurrence frequency → Frequency
 Occurrence rate 271, 274, 539
 Occurrence time → Arrival/occurrence time
 On line (without operational interruption) 2, 9, 41, 112, 120, 124, 170, 171, 196, 202, 239, 390, 393, 397
 One-item structure 39-41, 175-89, 240-43, 443

- One-out-of-2 redundancy **31, 43-44, 141, 196-213, 232, 233, 243-58, 271-74, 295-309, 504, 508-10, 526-30**
(in particular **44, 141, 196-99, 201, 213, 232, 233, 248, 256, 295-98, 302-09, 504, 508-10**)
- One (only one) regeneration state **171, 204, 207, 208, 240, 386, 494**
- One repair crew → Only one repair crew
- One-sided confidence interval → Confidence interval
- One-sided sampling plan (for p) **318-20, 567-68**
- One-sided tests to demonstrate λ or $MTBF=1/\lambda$ **336-37**
- One-step transition probability **194, 200, 496, 501, 521**
- Only one repair crew **170**; holds for all models in this book (see e.g. **208, 248, 256, 267**) often with no *FF*, except pp. **61, 217-18, 231, 232, 276, 280-85, 293-94, 504, 505, 517-21, 531-32** (see also Advantage)
- Operating characteristic curve **315-16, 319, 334, 336, 337, 340, 565-66, 568**
- Operating (field) conditions **3, 7, 26, 28, 33, 35, 79, 84, 90, 99, 102, 105, 156, 388, 401, 410, 415, 422**
- Operating console **149, 158**
- Operation monitoring **116, 117, 156, 249**
- Operational availability **13** → Overall availability
- Operational effectiveness **13**
- Operational profile (software) **28**
- Optical beam induced current (OBIC) **104**
- Optimal derating **33, 145**
- Optimization **120, 143, 370**
- cost **11-15, 67, 120, 137-40, 142-43, 376-83**
 - preventive maintenance period **137-38, 139, 140, 241-43, 250-51**
 - reliability allocation **67**
- Optoelectronic/Optocoupler **145, 146, 151, 372**
- Order (ed) observations/sample **339, 346, 347, 352, 542, 544, 574**
- Order statistic **355, 357-59, 366, 534, 535, 542, 544**
- Ordinary renewal process **292, 480, 482**
- Organization (company structure) **20, 400, 402**
- Orthogonal **454**
- Outcoming event **286**
- Outgoing quality (AOQ) **315-16, 379**
- Overall availability **9, 13, 14, 139-40, 242**
- Overflow **519**
- Overhaul **113, 119**
- Overstress/overload **33, 96, 103, 153, 271, 363, 371**
- Oxidation **83, 98, 371**
- Oxide **93, 96, 97, 102, 103, 106, 153, 345, 373, 588-89**
- P**ackage/Packaging **84-85, 89, 100, 104, 146-47, 345**
(see also Hermetic, Plastic)
- Pairwise independent/exclusive events **435, 436**
- Parallel model **31, 43-45, 58-60, 61-64, 196-219**
(see also One-out-of two, k -out-of- n)
- Parallel redundancy → Active redundancy
- Parameter estimation **312-14, 321, 323-24, 327, 328-32, 337-39, 365-66, 549-62**
(in particular **313, 324, 331, 549-51, 554**)
- Pareto **76, 78**
- Paris law **345**
- Part count method **51**
- Part stress method **27, 33-38, 50-51** (see also **69-71**)
- Particular semi-Markov processes **295, 296, 296-310**
- Partition
- data **38, 329, 350, 573**
 - item/states/tasks **13, 29, 90, 112, 115, 116, 154, 158, 164, 166, 295, 410-13, 437, 507**
 - life cycle **19, 160, 161, 328, 417**
- Partitioning cumulative op. time **328, 329, 335**
- Passivation/Passivation test **85, 89, 93, 100, 104-6, 147**
- Path **55, 58, 166**
- Path set → Minimal path sets
- Pattern sensitivity **91, 93**
- Pay attention → Care
- PCB → Populated printed circuit board
- Pearson / Pearson theorem **555, 573**
- Percentage point **450**
- Perfective (software) **161**
- Performability **259, 266, 270-71, 517** → Capability
- Performance effectiveness → Reward
- Performance parameters/test **84, 86, 108, 422**
(see also Characterization)
- Petri nets **287-88**
- Phased-mission systems **28, 30, 38, 259-71, 392**
- Physical models → Model valid., Physics of failures
- Physics of failures **38, 345** (see also Failure mech.)
- Piecewise definition **440, 583**
- Pilot production **19, 108, 363, 364, 369, 386, 389, 398**
- Pinholes **93**
- Pitch **84-85, 109, 111, 152**
- Plastic packages **85, 89, 98-100, 102, 104, 147, 153**
- Plasticity **69** (see also Viscoplastic)
- Plug-in / plug-out **116, 151, 157**
- PM* → Preventive maintenance
- PN → Petri nets
- PoF → Physics of failures
- Point availability ($PA_{S_i}(t)$, $PA_S = AA_S$) **9, 177, 386**
- computation **9, 61, 172-73, 177, 183, 184, 185, 188, 191, 195, 197-98, 201, 213, 217, 232, 233, 278, 293-94, 507-08, 511, 529, 530, 531-32**
 - definition **9, 177, 184, 386, 492, 507-08, 524**
 - demonstration **325-26, 327, 569-71**
 - estimation **323-24, 327, 561-62**
 - with preventive maintenance **242**
- Point estimate at system level (λ_{S0}) **332**
- Point estimation **312, 323, 329, 330, 365-66, 549-53, 558, 562** (see also Empirical, Max. likelihood)
- Point processes (PP) **168, 354-62, 480, 532, 536-40**

- Poisson approximation 10, 316, **318**, 334, 467, **468**
- Poisson distribution **317**, 329, **446**, **467-68**, **552**, 578
- Poisson's integral 462, 464, **582**
- Poisson processes
- homogeneous (HPP) 7, 35, 142, **328**, 329-30, **353-54**, 357-62, 393, **480**, 483, **488-89**, 532-36, 538-40
 - nonhomogeneous (NHPP) 138-39, 168, **353-54**, **355-56**, 357-62, 364-68, **489**, **532-36**
 - NHPP versus HPP **533**, **536**
 - simulation **291**, **536**
 - tests **355-62**, **363-68**, **536**
- Populated printed circuit board (PCB) **23**, **27**, **84**, **85**, **90**, **94**, **108-11**, **116**, **149**, **151-53**, **154-59**, 369-70, **374-76**
- Portability (software) **162**
- Possible causes
- common cause failures **66**, **271**
 - defects / latent failures **106-07**, **108-11**, **148**, **162-63**
 - single point failures **66**
- Potential reliability problem **94**, **95**, **106-07**, **110**
(see also Damage, Weaknesses)
- Power devices **98**, **146**, **150**, **151**, **152**
- Power Law / Power Law process 276, 345, **364**
- Power of a (statistical) test **357**, **564**, **572**
- Power supply **28**, **96**, **108**, **148**, **150**, **151**, **155**, **157**, **230**
- Power-up / power-down **96**, **150**, **151**
- PP → Point process
- ppm **371**, **462**
- Practical aspects for MTBF & MTTR demonstration **335**, 339-40, **408-409**
- Practical examples → Examples, Numerical
- Predicted maintainability **121-25**
- Predicted reliability **3**, **25-27**, **28-71**, **169-298**, **410-11**
- Predicted safety (safety function) **303-09**
- Preferred part list (PPL) → Qualified part list (QPL)
- Preheating **153**
- Preliminary design reviews **419**, **422-24**
- Preliminary/rough analyses **18**, **51**, **408**, **410**
- Premature wear-out **345**
- Pressure cooker → HAST
- Preventive actions/measures **16**, **22**, **72-79**, **120**, **144-66**, **295**, **369-70**, **371-74**, **375-76**, **409-20**, **421-25**
- Preventive maintenance **8**, **112-13**, **125**, **134-40**, **240-43**, **249-51**, **310**, **395**, **443**
- Primary failure/fault **4**, **76**, **538**
- Printed circuit/wiring board → Populated printed circuit b.
- Priority / priority list (software quality attributes) **160**, **164**, **416**, **424** (see also Repair priority)
- Probability **431-34**
- Probability chart **347-51**, **459**, **541**, **547-48**, **585-87**
- Probability density → Density
- Probability plot paper → Probability chart
- Probability space **429**, **433**, **435**, **450**, **471**, **477**
- Problems for homework **592-99**
- Procedure for (see also Rule for)
- analysis of binary decision diagrams **283-85**
 - analysis of complex rep. systems **277-79**
 - analysis of large complex rep. systems **293-94**
 - analysis of mechanical systems **68**, **69**
 - analysis of phased mission systems **262**
 - Anderson-Darling/Cramér-von Mises test **572-73**
 - binary decision diagram's drawing up **283**
 - chi-square test **350-52**, **573-75**
 - cost optimization (quality & RAMS ass.) **12-14**
 - cost optimization at incoming inspections **279-83**
 - demonstration of
 - availability ($PA=AA$) **325**, **570**
 - MTTR **339-40**, 409
 - probability p **315**, **317**, **318**, **319**, 321, **565**
 - λ or $MTBF \equiv 1/\lambda$ **333**, **334**, **336**
(in particular **317**, **326**, **335**)
 - double one-sided sampling plan **319**
 - electrical test of complex ICs **88**, 90-93
 - environmental test for assemblies (PCBs) **108**
 - environmental test for complex ICs **92-100**
 - ESD test **94**
 - estimation of
 - availability ($PA=AA$) **323-24**, **561-62**
 - MTTR **337-39**
 - parameters 365-66, **550-51**
 - probability p **312**, **321**, **551**, **555**, **557**
 - λ or $MTBF \equiv 1/\lambda$ **330-31**, **551**, **553**, **558-61**
(in particular **313**, **324**, **331**)
 - event trees **286**
 - failure analysis **105**
 - first delivery **394**
 - FMEA / FMECA **73**, 74-75
 - frequency / duration **278-79**, **514-17**
 - goodness-of-fit tests **571-76**
 - graphical estimation of $F(t)$ **347**, **346-51**, **546-47**
(see also 361-62, 363-68, 484, 571-73, **585-87**)
 - incoming inspection **379-83**
 - Kolmogorov-Smirnov test **347**, **356**, **366**, **572**, **574**
 - Laplace test **358**, 360
 - maintenance **112-13**, 116-20, 409
 - mechanical system's analysis **68**, **69**
 - modeling complex rep. systems **277-79**, **293-94**
 - phased-mission systems investigation **262**
 - qualification test for assemblies **108-11**
 - qualification test for complex ICs **87**, **89**
 - qualification test for first delivery **384**
 - quality and reliability (RAMS) assurance **17-20**, **21-24**, 401-05, **407-25**
 - quality cost optim. at incoming inspection **376-83**
 - reliability allocation **67**
 - reliability prediction **2-3**, **26-27**, **52-53**, **67**, **68-69**, 170-71, 238-40, **277-79**, **293-94**, **410-11**

- reliability test
 - accelerated tests 341-46
 - statistical aspects 321-37, 346-68, 541-76 (in particular 317, 326, 331, 335)
 - technical aspects 101, 111, 370-76, 408-09
 - screening of
 - assemblies 375
 - components 371-74
 - sequential test 317, 334-36, 566-67
 - simple one-sided sampling plan/test 318, 336, 565
 - simple two-sided sampling plan/test 315, 333, 565 (see also Sequential test)
 - simulation of stochastic processes 291-92, 536
 - software development & test 162-65 & 166-68
 - test and screening 87-111, 370-83 (in particular 89, 372, 379-83)
 - transition probabilities determination 172-73, 502, 522-23, 527-30 (see e.g. 200-01, 204-05)
 - transition rates (determination of) 173, 277-78, 499-503 (see.g. 197, 203, 217, 235, 246, 258, 267)
 - trend tests 358-61
- Process 477 (see also ARP, GPP, HPP, MP, NHPP, PP, RGP, RP, SMP, SRP)
- stationary 478-79, 487-88, 512-14, 524-25
 - time homogeneous (or with stationary increments) 479, 489, 532
 - with independent increments 355, 355-68, 477-78, 488-89, 532, 532-36, 540
- Process FMEA/FMECA 72, 78, 390
- Process reliability 3
- Procurement 370-71, 384, 411, 420
- Producer risk α 86, 315, 318, 325, 326, 333, 335, 564, 568, 570 (see also Type I error)
- Product assurance 16, 395, 403, 404
- Product liability 10, 15, 388, 395, 403, 418
- Production / manufacturing
- basic RAMS assurance activities 369-70, 412
 - documentation 417
 - flaw 26, 73, 77, 106, 109, 110, 111, 294, 363, 375
 - FMEA/FMECA → Process FMEA/FMECA
 - process 4, 6, 7, 10, 15, 19, 20, 21, 38, 78, 87, 98, 106-11, 152-54, 363, 369-70, 376-79, 389, 396, 400, 401, 405, 412-13, 416, 417, 424
 - related reliability problems 95, 106-07, 109-10
- Program/erase cycles 97, 372
- Program for quality & reliability (RAMS) assurance 17-19, 407, 409-20, 421-25
- Programmed reliability 406
- Project documentation 417
- Project management 19, 17-24, 160-61, 162-64, 414-15
- Project manager 19, 24, 300, 407, 414-15, 418, 428
- Project quality & reliability assurance manager 418
- Propagation (of events) 286
- Protection against
- common cause failures 66, 274
 - damage → Damage
 - electromagnetic fields 148, 149
 - ESD/EMC 94, 148-50
 - incomplete coverage 249, 254, 255
 - single point failures 42, 66, 79, 423
 - shorts / opens 3, 26, 29, 30, 32, 42, 51, 64-65, 100, 101, 107 (see also Design guidelines)
- Prototype 18, 19, 87, 108, 346, 363, 364, 377, 412, 415, 419, 420, 422, 424, 426
- Pseudo redundancy 42, 397
- Pseudorandom number 291-92
- PSG 93, 99, 100, 103, 106 (see also Passivation)
- Pull-up / pull-down resistor 120, 149, 150, 152, 156
- Purple plague 100, 103
- Quad redundancy 65, 66, 101
- Quadratic statistic 356, 572, 574
- Qualification tests 18, 87, 108, 363, 377, 412, 419
- assemblies 108-11
 - components 89, 87-107, 346
 - prototypes 346, 363, 364, 377, 412, 419
- Qualified part list (QPL) 87, 150, 411, 416, 423
- Quality 11, 16, 395
- Quality and reliability (RAMS) assurance
- department (Q & RA) 19, 20, 410-13
 - program 16, 17-18, 24, 401-05, 407, 409-28
 - requirements 401-05, 407-09
 - standards 401-06
- Quality assurance 11, 13, 16, 17-24, 144-68, 311-68, 369-84, 388, 396, 401-05, 407-28
- software 159, 160, 161-68
- Quality assurance handbook 20, 21, 401-05, 413, 428
- Quality attributes for software 160, 162
- Quality control 13, 16, 17, 18, 21, 311-20, 396, 412, 564
- Quality cost 12-15, 18, 20, 378-83, 400, 413 (see also Cost optimization)
- Quality data reporting system 13, 17, 21-23, 377, 396, 413, 420, 426-28
- Quality factor π_Q 36-37
- Quality growth (software) 166-68
- Quality of design 16
- Quality of manufacturing 16, 21, 86, 369-70
- Quality management 16, 20, 21, 24, 396, 401, 402 (see also Quality assurance, TQM)
- Quality manual → Quality assurance handbook
- Quality metric for software 160
- Quality test 13, 16, 17, 21, 396, 411-12, 418-20
- statistical aspect 311-20
- Quantile 338, 450, 545, 578-81
- Quick test 117

- Radiation** 82, 96, 103, 590
- RAMS** (Reliability, Availability, Maint., Safety) 17, 401
- assurance program/rules 19, 409-420, 421-28
→ Quality and rel. (RAMS) assurance program
 - definition & realization of requirements 407-20
 - engineering 16, 17, 24 → Reliability eng.
- Random cumulative operating time** 332, 553
- Random duration (mission)** 39, 261, 265
- Random numbers** → Pseudorandom numbers
- Random sample** → Sample
- Random variable** 439-41
- Random vector** 450-54, 476-79, 542
- Random vibrations** 83, 108, 109, 111, 375
- Rare event** 10, 289, 292
- RBD** → Reliability block diagram
- Reachability tree** 287-88
- Realization (time schedule/simulation) of a stochastic process** 176, 208-09, 219, 250, 291-92, 477, 480, 491, 522, 527-29 (see also Evolution)
- Realization of RAMS requirements**
→ Quality and reliability assurance program
- Realize an advantage (can)** 318, 336, 568
- Reason for** → Causes for
- Recognition** → Fault detection
- Reconfiguration** 66, 118, 164, 238, 259, 277, 514, 516
- failure censored 266-69
 - time censored (phased-mission system) 259-66
 - with reward and frequency/duration 270-71, 514
- Recrystallization** 109
- Recurrence time** 181-82, 185, 484-85, 492
(see also Rest waiting time)
- Recurrence time limit theorem** 486
- Recycling** 10, 19, 391
- Redesign** 8, 79, 81, 87, 363, 371, 405
- Reduced test** → Normal/reduced/tightened test
- Reduction** → State space reduction
- Redundancy** 31, 42-45, 49, 51, 53, 61-64, 65, 101, 159, 201, 213, 217, 232, 233, 235, 244, 248, 256, 259, 267, 274, 275-76, 284-85, 397, 411, 504-06, 508-10, 519-21, 527-29 (see also Active, One-out-of-2, k-out-of-n, Standby, Warm redundancy)
- for software 42, 49, 66, 159, 164-65, 274
 - limitations 101, 239 (see also Compromise, Effect)
 - practical aspects 32, 49, 51, 62, 64-65, 196, 239, 274
 - realization 30-32, 42-43, 44, 49, 51, 53, 54, 64-65, 66, 68-69, 101, 196, 235, 244, 267, 274, 275-76, 282, 411 (see also Mandatory)
- Reference documentation** 419, 424
- Reference failure rates** 35, 38, 408, 588-91
- Reflow soldering** 153
- Refuse to start** 246 (see also No start at call)
- Regeneration point** 176, 178, 182, 208, 220, 386, 480, 491, 494-95, 511, 522, 530 (see also Renewal point)
- Regeneration state** 41, 170, 171, 174, 193, 204, 208, 218, 223, 229, 239, 240, 386, 478, 494, 502, 522
- Regenerative processes (RGP)** 171, 207-13, 478, 494-95, 530 (see also Markov, Semi-Markov, Semi-reg.)
- Rejection line** 317, 334-36, 566-67
- Relation between** (see also Distinction between)
- asymptotic and stationary / steady-state 187, 488, 493, 495, 497, 513-14, 524-25, 530
 - distribution functions 461, 468, 578-80
 - P_i and \mathcal{P}_i 513, 524-26, 530
 - stochastic processes 171, 478, 521
- Relative frequency** 313, 431, 434, 471, 542, 551, 554
- Relative humidity** 98-99, 147, 153
- Relaxation** 109
- Release / released** 19, 20, 21, 87, 369, 387, 418, 419
- Reliability** 2-3, 13, 39, 170, 176, 184, 199, 397
(see also Assessed, Estimated, Predicted)
- allocation / optimization 67, 142, 408, 410, 421
 - analysis 13, 16, 25-79, 144-53, 169-294, 410-11, 415
(in particular 27, 31, 172-73, 201, 217, 233, 277-79;
see also Computer, Human rel., Risk analysis)
 - approximation (gen. procedure) 232, 233, 293-94
 - as selection criterion 86
 - assurance → Quality & rel. assurance program
 - block diagram (RBD) 28-32, 42, 50-51, 52, 68-69, 235, 238, 267, 275-76, 283-84, 398
(see 240, 243-80 if the RBD does not exist)
 - block diagram with elements repetition → Same
 - conditional → Conditional reliability function
 - demonstration → Reliability tests
 - design guidelines 144-68
 - design review checklist 79
 - engineering 13, 16
 - estimation 4 (see also Reliability tests)
 - function 3, 39, 58, 63, 69-71, 172-73, 176, 184, 190, 199, 278, 397, 441, 442, 509, 511, 524
◦ with preventive maintenance 241-43
(see also Conditional rel. function, Rel. analysis)
 - growth 363-68, 398 (see also 166-68 for SQ)
 - improvement 26-27, 79, 144-54, 154-68, 407-28
 - interval → Interval reliability
 - long term behavior (components) 86
 - mechanical → Mechanical reliability
 - optimization 67 (see also Reliability allocation)
 - prediction → Rel. anal., Procedure, Computer-aid.
 - tests 35, 86, 89, 101, 109-11, 375-76
◦ statistical aspects (estimation & demonstration)
failure rate λ (or $MTBF \equiv 1/\lambda$) 328-37, 358-60
fixed mission (R) 321-22
◦ technical aspects 101, 111, 370-76, 408-09
 - weaknesses 3, 27, 72-79, 80, 321 (see also Damage)
 - with preventive maintenance 241-43
- Remote control/diagnostic/maintenance** 118, 120

- Renewal density 211, 356, **481**, **482**, 491, 525, 532
 Renewal density theorem 186, **486**
 Renewal equation **482**
 Renewal function **481**
 Renewal point **135**, **208**, **241**, **292**, **480**, **490**, **491**
 (see also Regeneration point **386**, **480**, **494**)
 Renewal points frequency → Renewal density
 Renewal processes (RP) 126, 135, 136, 171, 292, **354**,
 362, **480**, **479-89**, **494**, 536-37
 • embedded 211, **490**, **494**, **530** (see also Embedded)
 • simulation **291-92**
 Repair **8**, **112-13** 170-71, 363, **387**, **394**
 • frequency → System repair frequency
 • priority 141, **220**, 221, 233, **235**, 239, 246, 258,
 267, 272, 277, **504**, **506** (see also Strategy)
 • rate **115**, **171**, **174**, **177**, **206-07** (see also Shape)
 • strategy → Maintenance strategy
 • time **8**, **113-15**, 115-20, 121-24, **337-40**, **394**, 464
 Repairability **113** → Corrective maintenance
 Repairable item/system **5**, **6**, **41**, **169-310**, **503-10**, **526-30**
 Repairable spare parts **130-33** (see also Spare parts)
 Repairable versus nonrep. **41**, **202**, **390-91**, **392-93**, **442**
 Replaceability **157**
 Replacement policy **134**, **135-40** (see also
 Centralized, Decentralized)
 Reproducibility 16, **79**, 152, **416**, **419**, 421, **424**, **425**
 Requalification **87**
 Required function **1**, **2-3**, **8**, **9**, **27**, **28-29**, **32**, **41-43**, **49**,
 55, **56**, **128**, **162**, **213**, 259, **389**, **392**, **398**, **408**, **410**
 Requirements → Quality and reliability requirements,
 Reserve contacts **157**
 Reserve/redundant element/state **42-43**, **62**, **124**, **170**,
 196, **206**, **207-10**, **213**, **244**, **249**, **504**, **526**, **529**
 Reserve to technological limits **38** (see also
 Technological properties/limits/risks)
 Residual failure-free time → Survival failure-free time
 Resilient → Fault tolerant, Graceful degr., Reconfig.
 Resistor **145**, 150, 151, **372**, **588**
 Rest waiting time **355**, **533** (see also Recurrence
 time, Waiting time paradox)
 Restarts anew **178**, **208**, **220**, **363**, **390**, **478**, **480**, **494**
 Restoration **8**, **112**, **113**, 171, **337**, **387**, **394** → Repair
 Restoration frequency → System repair frequency
 Restoration time **113** → Repair time
 Results (tables/graphs) **31**, **44**, **47-48**, **127**, **141**, **183**,
 188, **195**, **201**, **213**, **217**, **227-28**, **232**, **233**, **237**, **241**,
 248, **256**, **265**, **269**, **313**, **316**, **317**, **319**, **324**, **326**,
 331, **334-37**, **340**, **343**, **348-51**, **372**, **378**, **484**, **489**,
 548, **560**, **566-68** (see also Numerical examples)
 Reusability (software) **162**
 Reuse **10**, **116**, **119**, **130**
 Reverse bias **98-99**, **372**, **590**
 Revision → Overhaul
 Reward / Reward rate **266-67**, **270-71**, **279**, **514**, **517**
 Rework **109**, **153**, **375**, **413**, 427
 RGP → Regenerative processes
 Right continuous **5**, **242**, **439**, 450, 457, 481, 532, **543**
 Rise time **88**, **94**, **148**, **149**
 Risk **9-11**, 13, 72, 107, **299**, **398**, 407, **411**, **423**
 • acceptance **10**, **310**
 • analysis / modeling **9-11**, **13**, **286**, **301-09**, **411**
 • assessment **10**, **294**, **301**, 309-10
 • avoidance **107**, 301-09, **309-10**
 • awareness / perception **11**, **300**, **310**
 • development / production / technological **10-11**,
 67, **81-82**, **84-86**, **106-07**, **271**, **363**, **407-28**
 • management **10-11**, **13**, **15**, **19**, **79**, **87-101**, **108-11**,
 120, **144-68**, **299-310**, **363-68**, **398**, **402-05**, **407-**
 28 (see also Feasibility, Redundancy, Fault effect)
 • management process **300-01**
 • mitigation **10**, 301-09, **309-10**, 399
 • priority number / importance measure **10**, **299**, **300**
 (see also Confidence level, Consumer risk, Fail-safe,
 Producer risk, Type I/II error)
 Robustness (software) **162** → Defect tolerant
 ROCOF 389, 540
 Rough analysis **51**, **362**, **408**, **410**, **419**
 RP → Renewal process
 Rudra's model **345**
 Rule for (see also Avoid, Procedures, Test plan)
 • check at failure **249**, **250**, **254**, **255**, **256**
 (see also Check strategy)
 • common cause failures **66**, **273**, **274**
 • convergence of $PA(t)$ to PA **183**, **186-87**, **198**
 • convergence of $R_S(t)$ to $e^{-\lambda_S t}$ **199**
 • critical decisions/failures (see also Critical)
 • data analysis **354**, **368**
 • derating **33**, **145**
 • design **66**, **144-68** (see also Care, Design)
 • dwell time **98**, **108**, **109**, **111**, **373**, **375**
 • essential parts **66**
 • firing **287**
 • FMEA / FMECA **73**
 • imperfect switching **245**, **246**, **247**, **248**, **257**
 • incomplete coverage **249**, **250**, **254**, **255**, **256**
 • junction temperature **37**, **146**, **150**
 • Markov processes / models **498**, **503**, **522**
 • modeling large or complex systems, **238-40**,
 277-79, **293-94**
 • partition of cumulative op. time **329**, **335**, **409**
 • phased-mission systems **262**
 • power-up / power-down **150**, **151**
 • quality and reliability (RAMS) assurance **19**
 • redundancy **44**, **46-47**, **66**, **226**, **248**, **250**, **254**, **256**
 • regenerative processes **394**
 • reliability growth **363-68**

- risk avoidance/mitigation **310**
 - semi-Markov processes **521, 522**
 - semi regenerative processes **494, 530**
 - series/parallel structures **45, 46, 226, 233**
 - software defect models **167-68**
 - software quality assurance **159-66, 167**
 - test time (cumulative operating time T) **335, 409**
 - use of ICs in plastic packages **85, 147**
 - (see also Conditions, Design guidelines, Influence, Mandatory, Procedure, Qualification, Screening)
 - Run-in **375, 386, 399** → Burn-in
 - Run test **166** (see also Debug test)
- Safety** **1, 9-10, 13, 15, 66, 158, 259, 294, 399, 403, 405, 411, 418, 423**
- analysis / assurance / improvement **9-10, 66, 72-80, 158-59, 294-98, 299-310, 399, 411, 415**
 - engineering (safety and human aspects) **13**
 - factor **69**
 - function ($S(t)$) **303, 304-09**
- Same element(s) in the reliability block diagrams **30, 31, 32, 53-56, 57, 58, 60, 68-9, 275-6, 284, 285, 290**
- Same stress **71**
- Sample **311, 541, 542, 554**
- with/without replacement **465/470**
- Sample path **477**
- Sample space (Ω) **429-30, 431, 563**
- Sampling tests/plans ($p, R, PA, \lambda, MTBF \equiv 1/\lambda, MTTF$) **311-40, 346-61, 379-83, 541-76**
- Scale parameter **458**
- Scan path **156-57**
- Scanning electron microscope **95, 104, 105, 107**
- Schmitt-trigger **92, 148**
- Scrambling table **91**
- Screening **6-7, 13, 26, 27, 79, 363, 370**
- assemblies **79, 80, 109-11, 375-76** (see also ESS)
 - components **35, 79, 82, 89, 101, 371-74, 423**
 - (see also Early failures, ESS, Strategy)
- Screening strategy → Strategy
- Seal test **373-74**
- Second source **79, 82, 87, 150, 423**
- Secondary failure **4, 66, 73, 271, 274, 310, 427, 538**
- Selection criteria for
- electronic components **81-86, 150, 411, 416, 588-91**
 - materials **411, 416**
 - special manufacturing processes **152, 412, 416**
- SEM → Scanning electron microscope
- Semidestructive analyses/tests **104, 105, 346**
- Semi-Markov processes (SMP) **6, 9, 167, 170, 171, 172, 192-95, 223, 240, 252, 279, 287, 292, 386, 394, 478, 490-93, 500, 502, 521-25, 530**
- particular **295, 296-98, 302, 302-09**
 - simulation **291-92**
- Semi-Markov process embedded → Semi-regenerative process, Embedded semi-Markov process
- Semi-Markov transition probability **172, 192-94, 200, 222-23, 252, 296-98, 303-09, 501-02, 521, 522-23, 527-29, 530**
- Semi-regenerative processes (SRP) **170, 171, 204-07, 218-19, 222-25, 240, 478, 494-95, 526-29, 530**
- Sensing/sensing devices **73, 295**
- Sensitivity **82, 84, 90, 91, 96, 109, 153, 290, 301**
- Sequential test **317-18, 334-36, 566-67**
- Series element → Effect, Influence
- Series model/structure/system **31, 41-42, 121-24, 189-95, 343-44, 354, 376, 444, 456, 458, 459, 536**
- Series-parallel model/structure/system with independent elements **31, 45-51, 52, 68-69, 123-24, 141, 220-37, 285, 288, 506**
- Series production **19, 363, 369, 374, 375, 389, 398, 412**
- Serviceability **113** → Preventive maintenance
- Services reliability **3**
- Set operations **430**
- Shannon decomposition **53, 58, 281, 283-85**
- Shape of the
- failure rate **7, 349-50** (see also Model)
 - renewal function **483-84**
 - repair time distribution **114, 174, 206-07, 240**
- Shape parameter **183, 458**
- Share of the failure rate **252, 256**
- Shewhart cycles **76**
- Shield/shielded enclosure **148, 149**
- Shmoo plot **91, 93**
- Shock **83**
- Short-term test **346** (see also HALT, HASS, HAST)
- Shut-off circuitries **310**
- Silicon nitride glassivation → Passivation
- Silver plated pins **94**
- Simple hypotheses **563**
- Simple one-sided sampling plan (p) **318-19, 567-68**
- Simple one-sided test (λ or $MTBF \equiv 1/\lambda$) **336-37**
- Simple structure **28, 31** (rows 1-6), **39-51, 175-237**
- Simple two-sided sampling plan (p) **314-16, 565-66**
- Simple two-sided test (λ or $MTBF \equiv 1/\lambda$) **332-35**
- Simplicity (software) **162**
- Simulation → Monte Carlo, Realization of a stoc. proc.
- Single-point failure **42, 66, 79, 423**
- Single-point ground **148**
- Six- σ approach **462**
- Skill **8, 144, 158, 159, 163, 376, 394,**
- Sleeping state → Dormant state
- SMD/SMT **84, 109-11, 152-53, 375**
- reliability test & screening **109-11**
- SMP → Semi-Markov process
- Sneak analyses **76, 79, 415**
- Soft error **89, 97**

Software

- attributes (quality attrib.) 160, 162, 164, 416, 424
 - causes for defects 162-63, 271
 - common cause faults/failures 271, 274
 - configuration management 160, 164, 165, 412, 417-19, 424, 425
 - defect modeling 166-68, 367-68
 - defect prevention 159, 162-65
 - defect tolerant 159-66, 162, 164-65, 416-17, 424
 - defects localization/elimination 117, 154, 166
 - design guidelines for SQ 159-63, 164, 165-66, 167-68
 - design reviews 160-61, 165, 417-19, 424
 - development procedure 160-61, 163
 - documentation 161, 162
 - element / module 161-63, 164-66, 424
 - embedded 159, 164
 - error correcting codes 159-60, 164-65
 - errors/defects at start ($t=0$) 167-68, 368
 - failure rate 159, 166, 167
 - fault 159, 391, 416
 - FMEA/FMECA 72-73, 160
 - freedom (reliability) 162
 - interaction 159, 163, 164
 - interface 161, 163, 164, 422, 424
 - life-cycle phases 160, 161, 417, 424
 - maintainability 162 (see also Perfective)
 - metrics 160, 162
 - module \rightarrow element
 - object oriented 164
 - packages 160, 162, 289, 290, 368, 399, 428,
 - partition 163, 164, 166, 417
 - quality 13, 17, 21, 160-62, 398, 399, 412, 416, 424
 - quality assurance 13, 21, 159-68, 416-17, 424
 - quality growth 166-68, 367-68, 424
 - redundancy 66, 159, 164-65
 - reliability \rightarrow Software defect freedom
 - specifications 161, 163, 164, 165, 416, 424
 - standards 160, 165, 403, 404, 621
 - test/validation 161, 163, 164, 166
 - test strategy 166, 416-17, 424
 - testability 162 \rightarrow Testability
 - time / space domain 159, 164
 - Validation 161, 163, 164, 166-67
- Sojourn time \rightarrow Stay time
- Solder joint 74-75, 84, 108-11, 153, 345, 374-75
- Solder-stop pads 152, 153
- Solderability test 89, 94
- Soldering temperature profile/stress 84-85, 152, 153
- Space domain 159, 164
- Space extension 531
- Spare parts provisioning 116, 118, 120, 125-33, 142
- Special diodes 150
- Special manufacturing processes 152, 416, 424
- Special tools 116, 120, 157, 413
- Specifications 3, 19, 28, 79, 88, 161, 163, 164, 165, 401, 410, 414, 417, 418, 419, 424-25
- Specified $p, \overline{PA}, \lambda, MTBF$ 315, 325, 333, 408
- SQ \rightarrow Software quality
- SRP \rightarrow Semi-regenerative process
- Standard deviation 449
- Standard industrial environment 35, 36, 37, 152, 591
- Standard normal distribution 126, 312, 339, 358, 446-47, 462, 472-75, 487, 550, 556, 577, 587
- Standardization 38, 118, 120, 154, 159, 401, 424
- Standardized random variable 449, 462
- Standards 9, 20, 35-38, 72, 78, 79, 82-83, 87, 94, 148, 160, 162, 165, 299, 300-01, 318, 320, 334, 335, 371, 385, 422, 423, 401-05, 620-22
- Standby redundancy 43, 62, 63, 201, 212, 213, 217, 218, 243-44, 397, 456 (see also Active, Warm)
- Standby time 242
- State clustering \rightarrow State space reduction
- State merging \rightarrow State space reduction
- State probability 62, 172-73, 197, 497, 499, 507, 508, 513-14, 523-24, 525, 530
- numerical examples 237, 269
- State space 56, 174, 192, 476-79, 496, 498, 507, 521
- State space extension 193-95, 531
- State space method 56-57, 65
- State space reduction 174, 277 (see also Cutting)
- State transition diagram \rightarrow Diagram of transitions
- Static burn-in 373 (see also Burn-in)
- Static fault tree 76, 281, 282, 283, 285
- Stationary / steady-state 478 (see also Asymptotic)
- alternating renewal process 187-89, 492-93
 - behavior at system level 278
 - distribution / initial distribution 497, 513, 524-26
 - increments (time-homog.) 479, 488, 489, 532, 540
 - Markov chain 497
 - Markov process 172-73, 512-14, 526
 - one-item structure 187-89, 323-27
 - point process 539-40
 - processes 478-79
 - regenerative process 495, 530
 - renewal process 487-88
 - semi-Markov process 172, 524-25
 - system failure/repair frequency 278-79, 515-16
- (see also Equivalence between asymptotic & stat.)
- Statistical decision 542
- Statistical equilibrium \rightarrow Steady-state \rightarrow Stationary
- Statistical error \rightarrow Statistical risk
- Statistical hypothesis 563-64
- Statistical maintainability tests 337-40
- Statistical probability 433 (see also Law of large nr)
- Statistical process control 311
- Statistical quality control 16, 311-20

- Statistical reliability tests **321-37, 346-68, 541-76**
- Statistical risk **541** (see also α , β , β_1 , β_2 , γ)
- Statistically independent **435, 451** → Independent
- Status / status test **116, 117, 119, 158, 249**
- Stay time (sojourn time) **61, 170, 171, 173, 239, 251, 260, 271, 277, 291, 295, 301, 394, 477, 490, 496, 500-03, 507, 514, 517, 521, 523-26, 530**
- Steady-state → Stationary / steady-state
- Step function **5, 440, 480, 543** (see also Unit step)
- Step-stress tests **346**
- Stiffness **109, 375**
- Stirling's formula **353, 582**
- Stochastic demand **181**
- Stochastic evolving network **276**
- Stochastic matrix **496, 498**
- Stochastic mean value theorem **495**
- Stochastic Petri net **287**
- Stochastic processes **61-64, 169, 171, 172-3, 476-540**
- Stochastically independent **435, 451** → Independent
- Storage / transportation **153**
- Story of reliability **405-06** (see also Historical develop.)
- Strategy
- cost optimization **142-43, 376-83, 466** (see also cost)
 - incoming inspection **378-83**
 - maintenance **35, 125, 134-41, 240-56, 257-74, 443** (in particular **141, 248, 255, 256, 274**)
 - screening **371, 372, 375, 376-77**
 - spare parts provisioning **125-33**
 - test **21, 120, 166, 371, 376-78, 255, 380-83, 418-20**
 - test & screening **21, 375, 376-83, 396, 411, 418-20** (see also Check strategy, Cost)
- Stress factor **33, 86, 144-45, 150-51, 388** (see also Derating)
- Stress-strength method **69-71, 76**
- Strict liability → Product liability
- Strict sense stationary **478**
- Strictly increasing/decreasing failure rate **137-39, 241, 242, 442, 458, 460**
- Strong law of large numbers **472, 543, 544**
- Strongly consistent **549**
- Structure function **58, 59, 283-85, 293** (see also Fault tree)
- Stuck-at-state **245-47, 248, 257-58, 266-69**
- Stuck-at-zero/at-one **90, 91**
- Student distribution (*t*-distribution) **579**
- Subcontractor **26, 415, 420** (see also Supplier)
- Subset **430**
- Successful path method **55-56, 69, 290**
- Successive approximation **316**
- Sudden failure **4, 6, 26, 134, 138, 427**
- Sufficient statistic/estim. **312, 330, 358-61, 549, 550-52**
- Sum of
- distribution functions → Mixture
 - Homog. Poisson processes **10, 128, 330, 489, 537**
 - Nonhomog. Poisson proc. **330, 489, 534, 536, 536**
 - Point processes **540**
 - Random variables **142, 180, 193, 347, 358, 393, 454-56, 460-63, 472-73, 538, 569, 571**
 - Renewal processes **537, 540**
- Superconform / superuniform **574**
- Superimposed processes → Sum
- Superposition → Sum
- Supplementary states/variables **193-95, 531**
- Supplier **15, 18, 105, 370, 384, 404, 411, 420, 423**
- Suppressor diodes **148, 149**
- Sure event **430** (see also Sample space)
- Surface mount devices/technique → SMD/SMT
- Survival failure-free time **442**
- Survival function **441** → Reliability function
- Susceptibility **148** → EMC
- Sustainable / sustainability **10, 16, 19, 391, 400, 404, 406, 407, 408, 422, 423**
- Switching / switching effect → Effect
- Switching element **49, 62, 220, 222, 243, 245, 257**
- Switching phenomena **79, 148, 149**
- Symmetry condition **477**
- Symptom → Failure mode
- Synonyms used in this book
- asymptotic & steady-state for stationary **187, 488, 493, 495, 513, 514, 524, 525, 530**
 - failure-free time for failure-free operating time **3, 39, 385, 440, 442, 457, 505, 542**
 - independent for mutually, statistically, stochastically indep. **435, 451** (see also Totally indep.)
 - mean for expected value **39, 445, 541**
 - reliability function for survival function **441**
 - repair for restoration **8, 113, 337, 387, 394**
 - sample for random sample **311, 541**
- System **2, 29, 39, 175, 277-79, 293-94, 399**
- confidence limits (on λ_S) **332**
 - design review **419, 421-25** (see also Design rev.)
 - down time → Down time, Mean down time
 - effectiveness → Cost effectiveness
 - failure frequency (f_{udS}) **270, 278, 515-16, 525**
 - failure intensity/rate **42, 43, 177, 193, 195, 332, 390, 279, 516, 536, 540**
 - function → Structure function
 - mean down time (MDT_S) **278-79, 394, 515-16, 525**
 - mean time to failure referred to state Z_i ($MTTF_{Si}$) **41, 173, 512, 524** → Mean time to failure
 - mean up time (MUT_S) **278-79, 394, 515-16, 525**
 - reconfiguration → Reconfiguration
 - repair frequency (f_{dus}) **270, 278, 515-16, 525**
 - restoration frequency → System repair frequency
 - specifications → Specifications
 - status → Status
 - up time → Up time, Mean up time

- without redundancy → Series model/structure
- Systematic failure **1,4,7,115,363,376-77,388,399,427**
- Systems engineering **11, 17, 19, 391, 400, 415**
- Systems with complex structure **31, 52, 52-66, 68-69, 238-79, 293-94, 295-309**
- Systems with hardware and software **168**
- Tailoring 17, 112, 376, 389, 407, 409, 410-13, 414**
- Take care → Care**
- Tasks / task assignment **17-21, 24, 28, 29, 113, 119, 158, 160, 161, 238, 295, 402, 409, 410-13**
- Tchebycheff → Chebyshev
- t*-distribution → Student's distribution
- Teamwork **10, 72, 78, 387** (see also Cooperation)
- Technical availability **242** → Overall availability
- Technical delay **113, 387, 394**
- Technical documentation **19, 417, 419, 424, 425**
- Technical safety → Safety
- Technical system **4, 399** → System
- Technological characterization
 - assemblies **108-11**
 - components **89, 90-101, 101-07**
 - prototypes **363, 412** (see also Prototype)
- Technological properties/limits/risks **10, 32, 38, 67, 81, 84-85, 87, 92, 96-100, 106, 108, 147-54, 341, 346, 363, 375, 407, 588-91**
- Temperature dependence **3,34-35,37,103,150-51,341-46**
- Terms used in RAMS engineering **162, 385, 386-400**
- Test (statistical for unknown)
 - availability **323-27, 561-62, 569-71**
 - distribution function **346-52, 542-48, 571-76**
 - *MTTR* **337-40, 409**
 - *NHPP* → Trend test
 - probability **311-20, 321-22, 353, 554-58, 564-68**
 - λ or *MTBF* $\equiv 1/\lambda$ **328-37, 352, 408, 551, 553, 558-61** (in particular **313, 317, 324, 326, 331, 335, 336**)
- Test (technical aspects, see also Accelerated tests)
 - assemblies **108-09, 374-76**
 - components **88-101, 370-74**
 - software **166**
- Test and screening procedure → Procedure
- Test and screening strategy → Strategy
- Test by attributes/by variables **311**
- Test conditions **83, 89, 93-101, 107-11, 370-76**
- Test coverage **90, 91, 117, 156** (see also Incomplete)
- Test level → Normal/reduced/tightened test**
- Test modi **156**
- Test pattern **90-93**
- Test plan/procedure **315, 317, 318, 319, 325, 326, 333, 335, 340, 347, 350-52, 358, 359, 360, 361, 565, 566, 567-68, 570, 572-75**
- Test point **120, 152, 156**
- Test power → Power of a test
- Test procedure → Procedure for test and screening
- Test stimuli **157**
- Test strategy → Strategy
- Test structure **97**
- Test time partitioning → Partitioning
- Test vector **88**
- Testability **79, 116-17, 150, 152, 155-57, 417, 419, 424**
 - software **162, 164, 166**
- Testing → Test
- TDDB → Time-dependent dielectric breakdown
- Theorem
 - addition **435, 437-38**
 - Bayes **438, 542, 549**
 - Blackwell **486**
 - central limit **126, 472, 473-75, 487**
 - Fubini **179**
 - Clopper & Pearson **555**
 - Elementary renewal **485**
 - Final value **583**
 - Fubini **179**
 - Fisher **575**
 - Glivenko-Cantelli **543**
 - Grigelionis **537**
 - Initial value **583**
 - Integral Laplace / De Moivre-Laplace **472, 556**
 - Key renewal **185, 186, 486, 493, 495**
 - Kolmogorov **545**
 - Korolyuk **531**
 - Limit theorems of probability theory **470-72**
 - Markov **497, 513**
 - Mean value **495**
 - Multiplication **436-37**
 - Pearson **555, 573**
 - Recurrence time limit **486**
 - Renewal density **486**
 - Stochastic mean value **495**
 - Strong law of Large numbers **472**
 - Tightened elementary renewal **485**
 - Total probability **438**
 - Weak law of Large numbers **471**
- Thermal cycles **89, 95, 98, 108-11, 371, 375**
- Thermal design concept/management **146**
- Thermal resistance **84, 85, 146-47**
- Thermal stress **150**
- Thermomechanical stress **147, 152**
- Three parameter Weibull distribution **459, 547-48**
- Three states **64-65, 150, 152, 248, 257-58, 266-69**
- Tightened test → Normal/reduced/tightened test
- Time censored reconfiguration → Phased-mission syst.
- Time censoring → Censoring
- Time compression **345**
- Time consuming **52, 72, 88, 114, 226, 236, 240, 259, 264, 289, 309, 316, 321, 512, 526, 531, 532, 592**

- Time-dependent dielectric breakdown **89, 96-97, 103**
- Time domain **159, 164**
- Time-homogeneous
- Markov chains **496**
 - Markov processes **7, 170, 172-73, 190, 196, 200, 201, 235, 239, 245, 248, 256, 257, 267, 277, 287, 291, 295, 478, 479, 494, 498-521, 522, 523, 526, 531**
 - Poisson processes → Poisson process
 - processes **477, 478, 479**
- Time redundancy **42, 164, 397**
- Time schedule (diagram) **135, 174, 176, 182, 208, 209, 219, 238, 240, 250, 279, 480, 491, 527, 528, 529**
- Time to market **11, 19, 387, 402, 407** (see also Market)
- Timing diagram/problem **151, 163**
- Tolerant → Defect, Failure, Fault
- Top-down **76, 78, 163, 164, 391** (see also Bottom-up)
- Top event **76, 78, 280-81, 283, 286, 391**
- Tort liability → Product liability
- Total additivity **432**
- Total down time **123, 124, 181, 538** (see also MDT_S)
- Total expectation **453**
- Total operating time → Total up time
- Total probability **52, 70, 177, 438, 454, 485, 499, 511**
- Total probability theorem **438**
- Total quality management (TQM) **16, 17, 18, 19, 20, 21, 400, 402, 407**
- Total sojourn time → Stay time
- Total up time **180, 181, 184, 242, 538** (see also MUT_S)
- Totally exclusive events → Mutually exclusive events
- totally IE* → *Totally independent elements*
- Totally independent elements **52, 61, 76, 133, 141, 195, 217-18, 221, 226, 231, 232, 235, 237, 239, 276, 280, 281, 283, 284, 293-94, 531, 536**
- TQM → Total quality management
- Traceability **405, 418**
- Training → Motivation/training/training level
- Transformation of
- random variables **291, 444, 464**
 - stochastic processes **357-58, 531, 534-35**
- Transient phenomena **144, 148, 150, 363**
- Transistors **30, 32, 33, 34, 38, 50-51, 74-75, 96, 100, 103, 106, 145, 150, 372, 590**
- Transition diagram → Diagram of transitions
- Transition probability **172-73, 197, 199, 205, 224, 496, 498, 508, 509, 511, 521, 523** (see also Diagram of Transition probability)
- Transition rate **238, 270, 277, 278, 287, 290, 293, 499, 500, 501, 507, 509, 516, 517** (see also Diagram of)
- Transportation/storage **153**
- Travel time **203-04, 250, 257, 503, 527-28**
- Trend test **357-62**
- Triggered events **300, 301, 310, 538**
- Triplet **429, 439**
- True reliability **26**
- Truncated
- distribution / random variable **135, 140, 261, 291, 292, 444, 522, 584** (**71** for stress-strength)
 - sequential test plan **336**
- Truth table **88, 90, 92**
- Twisted pairs **149**
- Two chamber oven **98, 373**
- Two dimensional random vector **452**
- Two failure mechanisms **37, 64-65, 109, 343-44, 367, 375, 444** (see also Multiple failure mechanisms)
- Two failure modes **64-65, 257-58, 266-69** (see also Multiple failure modes)
- Two-sided confidence interval → Confidence interval
- Two-sided test / sampling plan
- availability $PA = AA$ **325-26, 569-71**
 - const. failure rate λ or $MTBF = 1/\lambda$ **332-36**
 - unknown probability p **314-18, 565-67** (in particular **317, 326, 335**)
- Two-step action **158, 294, 295, 310**
- Type I (time) / II (failure) censoring → Censoring
- Type I/II error (α / β) **315-20, 325-26, 332-37, 339-40, 346-52, 358-61, 563-64, 565-76** (see also Producer risk, Consumer risk)
- Ultrasonic cleaning **153**
- Unavailability **61, 202, 230, 311-20, 321, 323-27, 561-62, 569-71**
- Unbiased **312, 323, 330, 338, 339, 393, 394, 544, 545, 549-50, 551, 552, 553, 562, 571**
- Uncertainties **26, 71, 99, 300, 301, 309-10**
- Unconditional
- expected value (mean) **453**
 - probability **7, 356, 434, 441, 482, 532, 540**
 - stay time **523**
- Uncorrelated **454**
- Understandability / readability (software) **164**
- Undetected failure/fault time τ_{UFT} **249, 251, 443**
- Uniform distribution / uniformly distributed **291, 292, 357, 358, 360, 464, 465**
- Unify methods/models/data **35, 38, 161, 169, 170-71**
- Uninterruptible power supply (UPS) **230-37**
- Union of events **430**
- Unit step function $u(t)$ **252, 584**
- Unknown probability → Defective probability, Demonstration, Estimation, Test
- Unloaded redundancy **43** → Standby redundancy
- Unused inputs/outputs **150**
- Up, up states (u, U) **57-58, 61, 173, 176, 277-78, 490-91, 507, 524**
- Up time **123-24, 181, 242, 270, 326-27, 538, 561, 562** (see also System mean up time MUT_S)
- Upper bound **59, 61, 187, 240, 260, 280, 281, 293-4**

- Usability (software) **162, 289, 426**
- Use of (see also **Synonym**)
- indices \rightarrow Indices
 - $MTBF \equiv 1/\lambda \rightarrow MTBF \equiv 1/\lambda$
 - plastic ICs **85, 147**
 - $R(t_1, t_2) \rightarrow$ Interval reliability
- Useful life **8, 13, 14, 35, 39, 79, 81, 85, 113, 116, 119, 120, 125, 146, 147, 150, 151, 177, 393, 400, 589-90 (146, 150, 151, 589, 590 for components)**
- User / User doc. **13, 15, 19, 115, 116, 118, 154, 156, 158, 159, 161, 162, 164, 413, 417**
- V**alidation (software) **161, 163, 164, 167**
- Validity \rightarrow Model validity / **verification**
- Value Analysis **13, 400, 414, 417, 421, 422**
- Value Engineering **13, 400, 417**
- Variable resistor **100, 145, 151, 588**
- Variable (test by) **311**
- Variance **447, 448-49, 454, 539, 544-45**
- Vibrations **28, 36, 82, 83, 103, 108, 109-11, 345, 375**
- Viscoplastic **behavior/deformation 69, 109**
- Visual inspection **89, 93, 102, 104, 105**
- Voids **93, 95, 100, 103, 109, 110**
- Voltage bias/reverse bias **98-99, 100, 372**
- Voltage stress **32, 33, 34, 35, 96, 98, 103, 106, 145, 149, 150, 151, 345, 371, 373, 386,**
- Voter **49, 222, 282, 285**
- W**afer **97, 106, 107, 154**
- Wait time \rightarrow Stay time, **Travel time**
- Waiting redundancy \rightarrow Warm redundancy
- Waiting time paradox **486**
- Walk-through 165**
- Warm redundancy **43, 62, 196-200, 201, 213, 217, 248, 258, 397, 504, 527, 528, 529 (see also Active, Standby)**
- Warranty **21, 23, 150, 376, 378, 396, 412, 413, 416, 426**
- Wash/Washing liquid **153**
- Watchdog timer **164**
- Wave matching **151**
- Wave soldering 153**
- Weak law of large numbers **471**
- Weaknesses analysis/avoidance **3-4, 6, 23, 26-27, 66, 68, 69, 72-80, 144-59, 160-65, 239-40, 255, 271, 274, 321, 363, 409-28 (see also Design guidelines, Design reviews, Mandatory, Rules)**
- Wear-out/wear-out failures /wear-out period **3-4, 6-7, 8, 35, 74-75, 98, 100, 113, 116, 134, 138, 159, 240, 345, 348, 349, 354, 357, 362, 363, 367, 389, 427, 444, 459, 483-84, 544, 588**
- Weibull distribution **126-28, 347-50, 354, 364, 446-47, 456, 458-59, 547-48, 552-53, 586**
- Weibull probability chart **348, 449, 547-48, 586**
- Weibull process **364**
- Weighted sum **7, 12, 40, 344, 349, 380-83, 444**
(see also Cost / cost equations, Mixture)
- Whisker growth **153**
- Wide sense stationary **479**
- Wire wrap **157**
- Without aftereffect **354, 355, 368, 478, 489, 496, 532, 533, 536, 540 (see also Distinction)**
- Without interruption \rightarrow On line
- Without redundancy \rightarrow Series model
- Work-mission availability **9, 140, 142, 180-81, 538**
- Worst case analysis **76, 79, 151, 410, 422**
- X**-ray inspection **93, 104, 105**
- Z**ener diodes **145, 149, 150**
- Zero defects **86**
- Zero hypothesis \rightarrow Null hypothesis H_0
- $f_{ud} = f_{du} =$ system failure & system repair frequency in steady-state (stationary) **516**
- $h(t)/m(t)/z(t) =$ RP/NHPP/GPP density **481/532/540**
- $i = \sqrt{-1}$ **577, 583**
- $P_i = Z_i$ steady-state probability **513, 525, 530**
- $\mathcal{P}_i = Z_i$ steady-state prob. of the embedded MC **496 (footnote), 513, 524, 530 (bottom)**
- $R(t_1, t_2)$ or $R(t, t+\theta)$ **179** \rightarrow Interval reliability
- $Si =$ index for state Z_i entered at $t = 0$ **3, 169**
- $t_1, t_2, \dots =$ realizations of τ **4-5, 347-48, 351, 542**
- $t_1^*, t_2^*, \dots =$ points on the time axis **358-62, 533-36**
- $T_i, T_{ii} =$ mean steady-state sojourn time in Z_i , mean steady-state time between successive Z_i occurrences
- $o(\delta t) =$ Landau notation **499**
- 1-out-of-2 \rightarrow One-out-of-two redundancy
- 1-out-of-2: G \rightarrow One-out-of-two redundancy
- IR & no FF = one repair crew and no further failures at system down 229, 170**
- 6- σ approach **462**
- 85/85 test \rightarrow Humidity test
- α particles **103**
- $\alpha, \beta =$ producer/type I, consumer/type II risk **563-64**
- β_1, β_2, γ ($\gamma = 1 - \beta_1 - \beta_2 =$ confidence level) **554**
- $\eta_n = \tau_n^* - \tau_{n-1}^* \rightarrow$ Interarrival time **533**
- $\lambda =$ const. (time ind.) failure rate **6, 40, 390-91, 443**
- $\lambda_{S0} =$ const. (time ind.) system failure rate (see also Si)
- $\mu =$ constant (time ind.) repair rate **114-15, 207, 277**
- Π circuit **592**
- $\tau =$ failure-free (operating) time **440-41**
- $\tau' =$ repair time **113**
- $\tau_{\min}, \tau_{\max} \rightarrow$ Minimum, Maximum of τ_i **456, 343**
- $\chi^2 \rightarrow$ Chi-square **578**
- \wedge used for estimated (empirical) values **4, 311, 541**